

NVR

User Manual

CONENTS

CHAPTER 1 PRODUCT OVERVIEW	5
1.1 REAR PANEL	5
1.2 REMOTE CONTROL (ONLY FOR REFERENCE, SUBJECT TO THE PHYSICAL OBJECT)	
CHAPTER 2 NVR INSTALLATION & CONNECTION	8
2.2 CONNECTION DIAGRAM	٥
2.3 POWER SUPPLY CONNECTION	
CHAPTER 3 COMMON OPERATIONS OF NVR	
3.1 USE OF THE PROVIDED MOUSE	_
3.2 Using Virtual Keyboard	
3.3 PASSWORD	
3.4 System Login	
4.1 START WIZARD	
4.1.1 Start Wizard	
4.1.2 Network Configuration	
4.1.3 Date / time	
4.1.4 IP Camera	
4.1.5 Disk	
4.1.6 Resolution	
4.1.7 Mobile	
4.1.8 Summary	
4.2.1 Camera Quick Toolbar	
4.2.1 Camera Quick Ioolbar	
4.2.3 System Menu	
4.2.3.1 Unlock and Lock Screen	
CHAPTER 5 NVR SYSTEM SETTINGS	
5.1 CHANNEL	
5.1.1 Channel	
5.1.2 Live configuration	
5.1.3 Image control	
5.1.4 Record and Encode Settings	
5.1.5 Image Capture	
5.1.6 PTZ	
5.1.7 Video Cover	
5.2 Storage	_
5.2.1 Schedule	
5.2.1.1 Record schedule	
5.2.2 Storage	
5.3 ALARM	
5.3.1 I/O alarm	
5.3.2 Exception	
5.3.3 Combined Alarm	
5.3.4 Voice Prompts	
5.3.5 Deterrence	
5.3.7 Disarming	
5.4 EVENT	
5.4.1 Event Settings	73
5.4.2 LIST MANAGEMENT	91


5.4.3 Statistical analysis	103
5.5 NETWORK	
5.5.1 General	
5.5.2 Cloud services	
5.5.3 DDNS (Dynamic Domain Name Server)	
5.5.4 Email	
5.5.5 IP filter	
5.5.6 Platform Access	
5.6 SYSTEM SETTINGS	
5.6.1 System	119
5.6.2 Multi-user management	
5.6.3 Maintenance	128
5.6.4 IP Camera Maintain	134
5.6.5 Information	137
CHAPTER 6 AI SCENARIO	141
6.1 Crossing counting scenario	141
6.1.1 Channel	141
6.1.2 Group No	142
6.1.3 Search	
6.1.4 Setting-up	
6.2 FACE ATTENDANCE	
6.3 NON-MOTOR VEHICLE STATISTICS	
CHAPTER 7 PLAYBACK SEARCH AND BACKUP	152
7.1 USE OF THE SEARCH FUNCTION	152
7.1.1 Playback interface search and playback video recording	154
7.1.2 Sub-Periods	
7.1.3 Slice Playback	158
7.1.4 External files	159
7.1.5 Event search, playback, and backup	159
7.1.6 Picture search	161
7.1.7 Tag playback	162
7.1.8 AI	162
CHAPTER 8 REMOTE ACCESS THROUGH THE WEB CLIENT	172
8.1 BASIC ENVIRONMENT REQUIREMENTS OF THE SYSTEM	172
8.2 DOWNLOAD AND INSTALLATION OF THE WEB PLUG-IN	
8.3 WEB CLIENT MANAGEMENT	174
8.3.1 Preview interface	
8.3.2 Playback	178
8.3.3 Remote Settings	183
8.3.4 Local settings	183
CHAPTER 9 PLAY THE BACKUP VIDEO	185
CHAPTER 10 XI APPENDIX	188
10.1 FAQs	188
10.2 USE AND MAINTEN ANCE	
10.3 RANDOM ATTACHMENTS (SUBJECT TO THE PHYSICAL OBJECT)	190

SAFETY INSTRUCTIONS

Please read the following safety instruction carefully to avoid personal injuries and prevent the equipment and other connection devices from being damaged.

- The device should be used in compliance with local laws, electrical safety regulations, and fire prevention regulations.
- Use the power supply attached or specified by the manufacturer only. Never operate the equipment by using an unspecified power supply.
- Firmly connect the plug to the power socket. Do not connect several devices to one power adapter.
- Power off the device before connecting and disconnecting accessories and peripherals.
- The NVR should not be placed in a dusty field.
- The NVR should be placed in sealing condition with good ventilation and kept away from sunshine, rain and water. If the equipment is accidentally in contact with water, unplug the power cable immediately and contact your local dealer.
- The NVR includes HDD which produces large amount of heat during operation. Do not block the vents (on the top, bottom and both sides) for cooling the system during operation.
- Never place the NVR in an unstable location. The NVR may fall to cause serious personal injury or death.
- Keep the surface of the NVR clean and dry. Use soft cloth to clean the outer case of NVR and do not use liquid aerosol cleaners.
- If smoke, odor or noise rise from the NVR, turn off the power immediately, unplug the power cable, and then contact your local dealer.
- This product contains a coin/button cell battery. If the battery is swallowed, it can cause severe internal burns in just 2 hours and can lead to death.
- If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Keep new and used batteries away from children.
- Do not dispose of the battery into fire or a hot oven, or mechanically crush or cut the battery, which may cause an explosion.
- Do not leave the battery in an extremely high temperature surrounding environment, which may
 result in an explosion or the leakage of flammable liquid or gas.
- Do not subject the battery to extremely low air pressure, which may result in an explosion or the leakage of flammable liquid or gas.

Chapter 1 Product Overview



1.1 Rear Panel

No.	Item	Description
1	Power Switch	Power switch to turn on or turn off the NVR.
2	DC Power Input	Connect the included DC power adapter
3	AUDIO Output	Audio output port. Connect to audio output devices like speakers.
4	VGA Port	Connect a VGA monitor. Audio line input port.
5	HDMI Port	Connect to HDMI display device(s).
6	USB Port	Connect an external storage device for recording or backup
6	Reset hole	Under the USB port, keep press 10 seconds to load device to default factory settings
7	WAN Port	Connect to a router or network switch

8	LAN Port	Network interface, connect IP cameras. *It is strongly recommended to only one camera per PoE port. *It is strongly recommended to only one camera per PoE port.
9	RESET Button	Press and hold for 10 seconds with a pin to restore default settings
10	E-SATA	Support E-SATA storage HDD to record and backup.
11	Sensor, Alarm & RS485 Terminals	SENSOR & G: Connect to external sensors; ALARM: Relay output to external alarm devices RS485: Connect PTZ device, such as speed dome camera
12	Line in	Device intercom, microphone connect interface.

1.2 Remote control (Only for reference, subject to the physical object)

Number	Keynote name	Key function
1	1-0	Channel selection, the number key
2	ALL	Multi-channel display
3	Menu	Enter the main menu / return
4	Mute	Silent function
5	Sub menu	Enter the sub menu
6	A	Up button, volume adjustment
7	SEL	Select the key / Edit key, Confirm the selection operation
8	•	Left / right, reduce / increase the parameter value on the control bar and adjust the volume on the playback page
9	▼	Down key, Volume adjustment
10	44	Fast back key
11	>>	Fast forward key
12	>	Enter the video query menu; play the key
13		Video key

14	Stop the manual video recording; stop the playing
15	Pause key / round tracking keys




Chapter 2 NVR Installation & Connection

This NVR supports two 3.5" or 2.5" SATA hard disk drives.

CAUTION: DO NOT install or remove the hard disk drive while the device power is turned ON.


HDD Installation:

- **a)** Connect the data and power cables to the two hard disk drives and place the hard disk drives on the NVR case.
- **b)** Carefully flip the NVR case and secure the hard disk drives to the NVR with the eight (8) screws



Note: Above procedures are for reference only. The practical operation may be different depending on the NVR you purchased.

2.2 Connection Diagram



Note: Above diagram is for reference only. The practical connection may be different depending on the NVR you purchased.


2.3 Power Supply Connection

Caution: Use only the supplied power adapter that came with the NVR.

Connect one end of the power adapter to the power connector on the back of the NVR. Plug the other end of the power adapter into the wall outlet.




For some specific models, you may need to press the Power switch to turn on the power.



Chapter 3 Common operations of NVR

3.1 Use of the provided mouse



1. Left key

- Click to select the menu option
- o In the multi-screen view, quickly double-click a channel for full-screen view. Double-click the channel again to return to split-screen viewing.
- o Select a channel in the Live preview to open the Camera Quick Toolbar
- o Click and hold in preview mode to drag the slider and zoom

2. Right Button

- o In menus, scroll to move up / down through the menu content.
- While hovering over the volume control wheel, scroll to turn system volume up / down.


3. Scroll Wheel

- o In menus, scroll to move up / down through the menu content.
- While hovering over the volume control wheel, scroll to turn system volume up / down.

3.2 Using Virtual Keyboard


You will see the virtual keyboard automatically on the screen when you need to enter data, such as enter password, camera title, etc.

Click to toggle the keyboard to upper case



3.3 Password

For the first time when you run the recorder, you must be required to set your own password immediately in order to protect your privacy. Please be sure to record your username and password and save them in a secure place.




Language: Choose an available OSD language.

Device ID: Input the device ID in the parentheses. Default ID is 000000. If your device is not using a remote control, you can leave the default value.

New Admin Password: Set the administrator password. The password length should be between 8 and 16 characters and must include at least two combinations of uppercase letters, lowercase letters, numbers, or special characters.

Confirm Password: Re-enter the administrator password.


Unlock Pattern: You can enable Unlock Pattern for quick access to the system. Select "Enable" and then draw the pattern, confirm it twice, and the pattern password will be successfully set




Camera Activation Password: This password is used to activate cameras that are not yet activated and are connected to the NVR. If "Same as recorder's password" is not checked, you can customize the activation password for cameras. If "Same as recorder's password" is checked, the device's login password will automatically be used as the camera activation password.

Click "Apply" to enter the password reset settings page.

Click **Apply** to enter the login interface, enter the device login password and click Login to unlock to enter the NVR system.




When the system is locked, click **Pattern** to enter the pattern password unlock interface to unlock the device.



When the system is locked, if you forget the password, you can click **Forgot Password** to reset. **Note:** Using the wrong password for 5 consecutive times, the system interface will be locked for 3 minutes.

After the first login, enter the password reset setting page, enable the appropriate password reset mode and save. If you click the Cancel button without checking any reset mode, the password reset function will not be enabled.




- ① Security Question Configuration: This feature enables the modification of the administrator user's password through security questions. After enabling it, you need to select three questions from a list of 15 common questions and set the answers, with a maximum length of 64 characters for each answer.
- **②** Certificate of authorization: This feature allows the modification of the administrator user's password using a key. After enabling it, you need to click on "Export" to download the key file and certificate.txt to a USB flash drive.

3 Super code (Not recommended): This feature enables the modification of the administrator user's password using a super code. If you enable this recovery method, when you forget your password, you'll need to prepare the recorder's MAC address and the current system date, then contact the dealer from whom you purchased the device. They will provide you with a unique Super Code for your device.


3.4 System Login

Once the system password and password reset settings are completed, you can use the newly set password to log in to the recorder.

If you have enabled Unlock Pattern, you can draw the pattern you have set to quickly unlock the device.



You can also click **Password** button to switch to the password input interface. After entering the password, click **Unlock** to access the device.



Note: The system interface will be locked for 3 minutes after 5 consecutive logins with incorrect passwords.

Chapter 4 NVR Starting up


4.1 Start Wizard

4.1.1 Start Wizard

When you first use the device, the system will open the Start Wizard menu, allowing you to quickly customize the basic functions of the device.



4.1.2 Network Configuration



If the network connected to the device has a DHCP server, check the DHCP box, and the DHCP server will automatically assign all network parameters to the device. or manually set the following network parameters:

IP Address: IPV 4 address is the identity of NVR in the network. It consists of four sets of numbers between 0 and 255, separated by periods. For example, "192.168.001.100".

Subnet Mask: A subnet mask is a network parameter that defines the range of IPV 4 addresses that can be used in the network. Subnet addresses also consisted of four sets of numbers, separated by periods. For example, "255.255.000.000".

Gateway: The IPV4 gateway address of the network where the device is located, the default is 192.168.001.001.

IPv6 Address: The IPv6 address is the identity of the NVR in the network. It consists of eight sets of numbers between 0 and FFFF, separated by colons. For example, "ABCD: EF01:2345:6789: ABCD: EF01:2345:6789".

IPv6 Gateway: The IPV 6 gateway address of the network where the device is located. **DNS 1 / DNS 2:** DNS 1 is the primary DNS server, and DNS 2 is the standby DNS server. Usually just enough to enter the DNS 1 server address.

Port

Web Port: This is the port used for the remote clients to log on to the NVR (for example, using the Web client). If the default port 80 is already occupied by another application, change it. **RTSP Port:** This is the port where NVR is allowed to transfer live streams to other devices (for example, using a streaming player).

Https Port: Https port is the web browsing port, mainly for HTTPS services, is another HTTP that provides encryption and transmission through a secure port.

Note: WEB port, RTSP port and HTTPS port are integrated, and share one port, and the default is 80. **UPNP (Universal Plug and Play):** Short for Universal Plug and Play, enables NAT traversal rules for automatic port mapping, allowing external computers to access internal network devices, there by optimizing network efficiency. UPnP functionality requires router support. Before enabling UPnP, please configure the router and set parameters such as internal IP address, subnet mask, and gateway in the network basic configuration to match the router. If your router does not support UPNP, make sure the port forwarding is completed manually in your router.

Mapping Strategy: Choose "Manual" for mapping type, allowing users to edit external ports (ports on the router). If set to "Auto," it will randomly map an external port (different from the internal port). **PPPoE:** PPPoE is a protocol that allows the NVR to connect to the network directly through a DSL modem. Check the Enable PPPoE box, then enter the PPPoE username and password provided by the ISP.

Enable PPPOE: Enable/disable switch for PPPoE. When enabled, the NVR will restart to activate the PPPoE settings.


PPPOE Network Card Select: Select the LAN port corresponding to the dial-up connection. (Note: This option is not displayed in Single Address mode).

User: PPPoE user name.

Password: PPPoE password.

4.1.3 Date / time


This menu allows the user to configure the date format, time format Date and Time



Date Format: Select the preferred date display format from the drop-down menu. **Time Format:** Select Set the preferred time 24Hour or 12Hour display format from the drop-down menu.

NTP


When this function is enabled, the device will automatically synchronize the date and time of the selected time server. In order to ensure the normal use of this function, the device should ensure the normal access to the network.



Enable NTP and server address cannot be modified.

Note: The default time zone is the same as the RISCO server. NTP is enabled by default, and the server address is pool.ntp.org

DST (daylight-saving time)




DST (daylight saving time): Tick to enable if Daylight Saving Time (DST) is observed in your region. **Time Offset** (Time offset): the amount of time to offset for DST.

Time Mode (Daylight saving time mode): the daylight-saving time in weeks or in days.

Start Time / End Time (Start time / end time): the start time and end time for daylight saving.


The current interface parameters cannot be modified.

4.1.4 IP Camera




1. Click "Search" to search for IP cameras in the same network. Select multiple IP cameras you want to add and click the icon

Add to NVR. Enter the camera's user name and password to add the camera.



- 2. Enter the user name and password of the camera to add the camera.
- 3. Click icon to open the IP Camera Add menu, manually enter the camera information or select the IP Camera from the device list.



IP Address/Domain: IP address or domain name of the IP camera.

Port: The port of the IP camera.

Protocol: Select the protocol to be used for the add-in.


Connection Mode: Select the mode of the IP camera from the dropdown menu.

User Name: User name of the IP camera.

Password: Password of the IP camera.

Connect with default password: When checked, the camera connection will use the default password that has been set.

4.1.5 Disk



The drive needs to be formated when it is first installed on NVR. Select the drive and click the Format HDD icon to format the drive.

Overwrite: When the hard drive is full, use this option to overwrite old records on the hard drive. For example, if you select the 7-day option, only recordings from the past 7 days will be retained on the hard drive. To avoid overwriting old recordings, choose "Disable." If this feature is disabled, regularly check the hard drive status to ensure it is not full.


To prevent overwriting any old recordings, select OFF. If you have set Off on this feature, please check the HDD status regularly to make sure the HDD is not full. Recording will be stopped if HDD is full. We recommended leaving the **Auto** selection as this prevents your NVR from running out of storage space.

NAS HDD: To add your NAS disk.

Record to eSATA: If your NVR comes with an E-SATA port on the rear panel, you can enable to record the video to E-SATA HDD. This function only available when your E-SATA HDD has been connected to the NVR already.


4.1.6 Resolution

Choose an output resolution that matches your monitor. The NVR supports automatically adjusting the output resolution to match the optimal resolution of your monitor during startup. If you connect to a 4K HDMI monitor, you can select a maximum resolution of 4K (3840x2160). If you connect to a VGA monitor, do not select a resolution larger than 1080P (1920x1080).



4.1.7 Mobile


When the device is added to the RISCO server, through the mobile APP to realize the remote monitoring and management of the device.




4.1.8 Summary

On this page, users can check the system summary information set up in the Start Wizard and complete the launch wizard.

If the user does not want to display the startup wizard on the next system restart, tick "Don't show the start Wizard on next startup" and click Finish icon to save and exit.



4.2 Introduction of the real-time view interface



Status Icons		
Icon	Description	
	The camera is being recorded currently	
*	A motion alarm is happening	
\$	An intelligent or AI alarm is happening	
$\hat{\mathbb{C}}$	The external I/O alarm device is being triggered	

HDD Error Icons		
Icon	Description	
8	HDD is uninstalled or in error	
	HDD is unformatted	
	HDD is full	

The other prompt messages that may appear in the screen:

Off-line: The analog camera is disconnected.

No Camera: No camera has been added to the channel.

Decoding Failed: NVR does not support this IP camera compression standard, please change to H.264 compression standard.

Insufficient Resource: The decoding resources for previewing IP channels exceed the decoding specifications limit, or IP channels using MJPEG encoding type can only preview one IP channel, while other IP channels indicate insufficient resources.

Insufficient Bandwidth: Insufficient bandwidth, channel cannot be brought online.

Failed to connect to camera: Failed to establish connection with the IP camera.

Incorrect user name or password: The username or password for the IP camera is incorrect. Please enter the correct username and password.

Privacy Mode: The IP camera is enabled in the privacy mode.

Click to open the Quick Add menu to add an IP camera.

Click to edit the current channel parameters.

4.2.1 Camera Quick Toolbar

In live viewing, click the left button of your mouse on a connected camera to display the camera quick toolbar.

Note: The shortcut buttons that appear may vary depending on the camera model.




Icon	Function	Description
Ö	Manul Record	Click to manually record the channel immediately. If the manually recording is in process, the icon will be in red color. Click one more time to stop manual record.
0	Image Capture	Click to save a snapshot of the current camera image. Manual Capture must be enabled to use this feature. For details on enabling Manual Capture.
ightharpoons	Instant Playback	Click to play the latest 5 minutes recording of this channel
©	PTZ Control	Click to enter PTZ control panel, click to control zoom and focus of motorized varifocal lens
Θ	Digital Zoom	Click to zoom-in the channel. Scroll the wheel button of your mouse to zoom in and zoom out the image.
	Color Adjustment	Click to adjust the image color of the channel.
HD	Stream Switch	To switch the live view video stream between HD & SD. HD is mainstream images, SD is substream images.
\Box	Siren Switch	If your camera has a built-in speaker, click this button to turn on or turn off the alarm sound.
ŷ	White light	If your camera has white light LEDs, click this button to turn on or turn off the LEDs.
Q	Warning light	If your camera has warning light LEDs, click this button to turn on or turn off the LEDs.
Q	Intercom	Click to start two-way voice communication.


B	Tag button	It supports to fast search by adding a tag in live view. Tagging enables you to create a searchable, descriptive index of important events or points of interest within extensive video recordings.
Al	AI statistics	Hover the mouse upon the icon to view AI statistics when the AI function is activated in your NVR.
8	Privacy mode	While enabled or disabled privacy mode, during privacy mode enabled, preview and playback without images.
ල	In pick	This button is displayed when the camera is connected, and click the button to enter In-Pick mode (some cameras do not support In-Pick function, only some NVR models support In-Pick)
(Area focus	Click the button, use the mouse to preview the area. The camera lens will focus according to the sliding area.(Zoom camera support only)

4.2.1.1 In-Pick

After the device adds camera online, the In-Pick icon will be displayed in the preview channel shortcut and the playback operation menu. Click the button to enter the In-Pick mode setting page.



The preview/playback is paused, the system will automatically detect and identify and select the human type and model targets in the screen, click button to enter the In-Pick search page, automatically retrieve the screenshots stored in Pedestrian and Vehicle according to the screenshots selected in the AI playback, and show the search results of similarity match.



1. Search criteria: Show the search results according to the set conditions.

Channel: Select the channel need to be searched.

Period: Select the search period, the options include one hour before and after, today, two days before and after, seven days before and after, and user customization. For example, one hour before and after the selection, the entry search time is 19:00, so the search period is 18:00-20:00.

Start Before, Stop After: Select the time before and after playback, for example, select 5s and 60s respectively, the search results will start the playback 5s before the actual start time, and the playback will end 60s after the actual end time.

Sort By: Select the sorting method, you can select the time lifting order and the similarity lifting order to sort the search results.

Similarity: Select the similarity and search according to the set similarity.

Search: Start to search.

Search results presentation:

Sort By: Select the sorting method, you can select the time lifting order and the similarity lifting order to sort the search results.


- Thumbnail view: You can view the snapshots of the results.
- List view: The search results are displayed in the list.
- Details View: You can view the details of the search results.
- : You can switch to the pages to view the results.
- **2.** Playback and backup of search results: Click the snapshot and put it back in a small window. double-click the snapshot to enter the playback page, which is consistent with the system playback function (see Chapter 7 Search, Playback and Backup for specific functions).
- Playback and backup, click to enter the playback and backup.

4.2.2 Taskbar




Click button to select a different layout to preview different channels.

1. **Common layout:** You can select the regular layout split screen provided by the system (2,4,6,8split screen)



2. Custom View Settings: Click to enter the setting page to customize view settings.



On the setup page, the functions are as follows.

Add a custom layout, click and a new custom layout, enter the name and click Apply, the custom layout is added successfully.

Edit the custom layout name, and click to set custom layout name.


Delete the custom layout.

Click to select the rule split screen as the custom layout.

Merge, use the mouse slide to select a small window, click window into a large window

Cancel, after the merged window, click button to cancel the merged window and change it back to the original small window.

Auto Cycle: Click to start preview the channel in sequence.



4.2.3 System Menu

You are able to configure the NVR for Channel, Record, Alarm, Network, Device, System, AI, AI Scenario from **Start Menu Setup**.





4.2.3.1 Unlock and Lock Screen

Click Lock Screen icon to lock the system immediately.

If the system is locked, then click the right mouse button to call up the menu, and you can pop up the unlock window to unlock.

4.2.3.2 Shutdown


Click the **Shutdown** button from Star Menu, you're able to shut down, reboot or logout the NVR. Click **OK** button, system will require to input the user password to authenticate.






4.2.3.3 Switch User

Click in the taskbar, you can call up the user switch menu, select the user who needs to log in, enter the corresponding user password, click **Switch User**, the system will switch the user.



Chapter 5 NVR system Settings

This menu can be configured with channel, record, event, network and other parameters. Path: System menu->Setup.




5.1 Channel


In this section, you are able to manage the camera connection, live view display, camera's image, video parameters and capture, PTZ setup, video cover.

5.1.1 Channel

5.1.1.1 IP Channels




- 1. Click Add to realize the expansion and folding of the device search window
 - a. Click Search button to search and display the devices under the same LAN. Select one or more devices based on the search results, and click Add to input the corresponding information to complete the addition.
 - **b.** Multiple devices can be selected based on the search results. Click **Batch IP Modification** to set the correct information and modify the selected camera IP in batches.
 - **c.** Select **Automatic Camera Addition**, the device will automatically add the camera that is not added in the LAN to the channel




- **2.** Click **Advanced Setup** button to enter the password of the device to open the Advanced Settings page, where the following operations can be performed.
 - 3. Default Password: Set the default password for the device to connect the camera through Private / Onvif / RTSP protocol. The default password of Private protocol can be used to activate the unactivated camera. When Use the Admin password as camera activation / connection password is checked, Private protocol will activate / connect the connected camera using the device administrator password.
 - 4. Modify Camera Password: Change the password of the existing online camera.
 - 5. Priority of PoE Channels (POE model NVR support only).
 - (1). The POE channel is preferred. If the camera has been manually added to the channel, then the camera is connected to the PoE port corresponding to the channel, the original manually added camera will be replaced by the PoE access camera. (Not checked to remember my choice, only effective once)
 - (2). Manual addition is preferred. If the camera has been manually added to the channel, and then the camera is connected to the PoE port corresponding to the channel, the camera originally added manually will not be replaced by the camera connected to the PoE access.(Not checked to remember my choice, only effective once)
 - (3). If any priority is not enabled, when the channel has been manually added a camera, access the camera in the PoE port corresponding to the channel, and the popup indicates that the current channel has exists and ask whether to replace it.
 - 6. Restore IP Channel Connection: When the device mistakenly removes online channel due to the restoration of factory settings, it can add the original online camera back to all the channels with one key.

Note: This function does not take effect after the factory Settings are restored via **Factory Defaults**.

- 7. Export and Import Camera: Export added IPC information as backup for reimport or import into other devices (exported information does not include connection password)..
- **3.** Select the camera that has been added to the device, and click Delete button to delete the selected camera.
- **4.** Tick **Show Password**, enter the administrator password and display the camera connection password added to the device.



- **5.** Click **Search** icon to search for the online camera in the LAN, select the camera to be added, and enter the correct information to add it.
- **6. Protocol**: Select the protocol of the IP camera from the drop-down menu, including Private, Onvif and RTSP protocol.




7. **Connect Mode:** Select General or **Security** from the drop-down menu. Choosing General will use the HTTP port connection protocol. Select Security will use the HTTPS port connection protocol.

Note: If the camera does not support using the Https mode, the HTTP port will be automatically switched.

Mainstream URL: When you select the RTSP protocol, this option appears, so enter the main stream address to connect to the IPC.

Substream URL: When you select the RTSP protocol, this item appears, enter the substream address to connect to the IPC.



8. Click Mode drop-down box to select either Auto mode or ePoE mode.

Note: In automatic mode, the transmission bandwidth of 100Mbps supports the maximum transmission distance of about 120 meters. In ePoE mode, it limits the transmission bandwidth to 10Mbps to expand the transmission distance to about 230 meters. (To ensure transmission stability, the Cat5E or Cat6 network cable is recommended)

Camera Mode: Camera mode, support Auto, Normal, Fisheye three modes.

5.1.1.2 POE power

This interface can display the power used by IPC to access NVR through PoE, and can view the used PoE used power and remaining power of NVR in real time.



Actual power usage: PoE Power in used.

Remaining power usage: Remaining PoE power.

Total Power: Set total power, click the total power.



button, pop up the prompt box, then can be set to modify



Warning:


- 1. If larger power supply is replaced, it is recommended to set the remaining power to 80% of the current power supply to ensure that the power supply load is within a reasonable range.
- **2.** The power calculation formula is: power (W) = voltage (V) *current (A). For specific parameters of the power supply can refer to the annotation information on the power supply sticker

Notes:

- 1. Single PoE port can support maximum power output of 30W.
- **2.** If the output power of the connected device exceeds POE port, the power supply will be insufficient and the upper and camera will offline.

5.1.2 Live configuration


Configure IP camera live parameters.



Channel: Display of the channel name

Privacy Mode: Privacy mode. During privacy mode enabled, there are no images for preview and playback, and the setting page does not display preview images.

Setup: Click icon to enter the Settings page.



Channel Name: Set the channel name.

Date Format: Set the date format for the IP camera OSD display.

Time Format: Set the time format for the IP camera OSD display.

Refresh Rate: Set the refresh rate of the IP camera.


Show Name: Preview displays the IP camera channel name.

Show Time: Preview displays the IP camera time.

This page supports the display of date format OSD, time format OSD, and Cross-counting statistics OSD (Cross Counting function is enabled) in the image.

5.1.3 Image control

This menu is used to set the image parameters for IP camera.



Channel: Channel name.

Setup: Click to enter settings page.



Channel: Select the channel that you want to configure.

Image Mode: Set the camera image mode, total three modes.

Full Color Mode: When surrounding illumination is insufficient, the warming light is on.

Day / Night Mode: When surrounding illumination is insufficient, the IR light is on for

supplementary lighting. When surrounding illumination is sufficient, the IR light turns off and the IR light finish supplementary.

Smart Illumination: Intelligent light mode, when surrounding illumination is insufficient, alarm will trigger the warming light on, the alarm end of the warming light off.

White Light: In Full Color mode, set the lighting effect of the camera warming light effect, total four modes.

Automatic mode: Automatic mode, the camera automatically adjusts the intensity of the warm light according to the ambient illumination.

Manual: Fixed brightness value, the surrounding light.

Schedule: By setting schedule table to automatically switch the warming light.

OFF: Disable the warming light.

Sensitivity: Level from 0 to 3, the camera perception of surrounding light, the higher the value, the more sensitive.

Light Distance: The range is 0-100, white light is to adjust the brightness of the supplementary light in Manual mode, the higher the value, the higher the brightness.

IR-Cut Mode: In Day / Night Mode , set the camera IR-Cut switching mode in 5 modes.

Auto / GPIO Auto: Automatic control switch mode, color switch black and white by image judgment, black and white conversion color by photosensitive judgment.

Day / Color Mode: Force the color mode, do not switch between black and white.

Night / Black White Mode: Force black and white mode, do not switch color.

Image File (s) / **Image Control:** Similar to the automatic mode, control the color to black and black to color mode through the image Schedule or B/W.

Schedule: Switch between black and white and color through schedule settings. Enable this feature, you need to set the start and end time to enter the night vision.

IR-LED Control: Set the warming light effect of the camera IR light during night vision, there are three modes.

Smart IR: Intelligent control of supplement light intensity, according to the focal length, whether the picture is over explosive dynamic control of IR light.

Manual: Manual mode to fill the brightness of the set IR light.

OFF: Disable IR light.

Low Beam Light: The brightness of the first group of IR lights can be manually adjusted. (0~100, the IR light is not bright when set to 0, and the brightest at 100).

High Beam Light: The brightness of the IR light of the second group (if the camera supports) can be manually adjusted (0~100, the IR light is not bright when set to 0, and the light is brightest at 100).

Hue: Adjust the image tone.

Brightness: Adjust the image brightness.

Contrast: Adjust the image contrast ratio.

Saturation: Adjust the image saturation degree.

Sharpness: Adjust the image sharpness.

Anti-Overexposure: Image anti-overexposure function.

Vertical Flip: Flips the image upside down.

Horizontal Flip: Mirrors the image horizontally.

Corridor Mode: Optimizes the camera's vertical viewing angle for monitoring long, narrow scenes like hallways or corridors. Enable this mode if your camera is aimed along a corridor.

Angle Adjustment: Allows to set the flip angle.

Exposure Compensation: Set the exposure compensation, there are four modes.

WDR: Wide dynamic range in which the picture is uniformly balanced based on the setting and both light and dark areas can be clearly distinguished. (DWDR here for some models).

HLC: Highlight compensation in which the objects in the highlighted area are clearer in the picture. (applicable for some models).

Back Light: Backlight compensation in which the objects in the dark area are clearer.

Disable: Image will not be optimized with backlight on.

3D Noise Reduction: Reduce the noise in the image to make the picture more clear. There are three modes.

Automatic mode: Camera automatically applies noise reduction algorithms.

OFF: Disable noise reduction.

Manual: Make noise reduction according to the manually set noise reduction coefficient.

White Balance: White balance setting, there are two modes

Automatic mode: Adjust the white light with the default parameters of the program.

Manual: Manually set red, green and blue gain synthesis white light.

Shutter: Set the length of the shutter exposure, there are two modes.

Automatic mode: Based on the value of the currently set Time Exposure, the program automatically selects an appropriate exposure time.

Manual: Use the configured Time Exposure value.

Exposure Time: Set the exposure time to use in conjunction with the Shutter setting. If the Shutter mode is set to Manual, this value determines the fixed shutter speed. If the Shutter mode is set to Auto, this value sets the slowest shutter speed limit. The camera will automatically select the most suitable shutter speed between this slowest limit and the fastest speed displayed by the system for

proper exposure. For example, if set to 1/30, the shutter speed will automatically adjust within the range of 1/30 to 1/20000 for optimal exposure.

Defog Mode: Optimizes visibility on foggy days (Need camera support). There are three modes. **OFF:** Disable defog function.

Automatic mode: The camera automatically judges the effect of defogging.

Manual: Defist according to the manually set values.


Default: Click this button to restore the factory default settings for all image parameters.

5.1.4 Record and Encode Settings

This menu configures the image parameters for recording video or network transmission. Generally, main stream is the quality of the recorded video saved in the HDD. Substream is the preview video quality through remote access (such as Web clients and CMS). The mobile stream defines the preview quality of viewing through remote access using mobile device, setting the switch of the connected webcam's audio, the volume of the input and output, and the audio type.

5.1.4.1 Recording settings

This menu can configure the relevant parameters of the system record.




Record Switch: Select to enable recording in this channel.

Stream Mode: Select the recording type. If you select the dual stream, the system will record both main stream and sub stream. If selected main stream, the system will only record main stream video. **PreRecord:** This allows your NVR to capture video for several seconds before an event occurs. It is recommended to keep this enabled.

ANR (Automatic Network Replenishment): Normally, videos are stored on the NVR when the network connection between the NVR and cameras is working. With the ANR (Automatic Network Replenishment) function enabled, the camera will start continuously recording to its SD card if the connection is lost. Once the network is restored, the recordings on the camera's SD card will be transferred back to the NVR's storage. It is recommended to enable ANR if your camera supports this feature (Only main stream will records).

5.1.4.2 Main stream



Resolution: Determine the record to main stream type. Higher values offer greater detail. The default resolution is auto-selected by your NVR.

Frame Rate: Set the frame number of the main stream.

Encoding Format: List the supported codec for the connected camera. H.265 compresses. information more efficiently for better video quality at a given bandwidth. H.265+ offers even greater compression. H.264 requires higher bandwidth and offers less efficient compression. H.264+ provides additional compression compared to H.264. Please note that only some devices support H.264+ and H.265+. Please note that in the substream, some cameras also support the MJPEG format. If you choose this encoding format, during preview, only one channel of MJPEG encoding will be displayed.

Encoding Mode: For simple scenarios, such as gray wall, a constant bit rate (CBR). For more complex scenarios, such as busy streets, a variable bit rate (VBR) is appropriate.

Video Quality: Available only for VBR, this setting allows to select the recording quality, here are several options like **Lowest**, **Lower**, **Low**, **Medium**, **Higher**, **Highest**.

Config Mode: Select either User-defined mode to manually set the bitrate or Predefined mode to choose from predefined bitrate.


Bitrate: Determines the speed of data transfer used for video recording. Higher bitrates result in better-quality recordings but require more bandwidth. Adjust incrementally until satisfied with image quality.

Audio: Enables or disables audio recording if your camera supports it. Make sure to enable Audio streaming in the Audio Encoding section if you want to record audio.

I Frame Interval: This parameter sets the interval between I frames (keyframes) in the IP camera's stream. I frames are full frames, while other frames are encoded based on the differences from preceding frames (P frames or B frames). A shorter interval can improve video quality but may increase bandwidth usage.

ETR: ETR (Event Trigger Recording) allows to adjust codec stream parameters for recording based on whether an alarm is present or not. This optimization ensures that crucial events, such as motion detection or alarm activation, are captured with optimal quality and efficiency.

5.1.4.3 Sub stream



Resolution: Determine the record to sub stream type. Higher values offer greater detail. The default resolution is auto-selected by your NVR.

Frame Rate: Specifies the number of frames recorded per second. The default frame rate is auto-selected by your NVR.

Encoding Format: Lists the supported codec for the connected camera. H.265 compresses. information more efficiently for better video quality at a given bandwidth. H.265+ offers even greater compression. H.264 requires higher bandwidth and offers less efficient compression. H.264+ provides additional compression compared to H.264. Please note that only some devices support H.264+ and H.265+. Please note that in the substream, some cameras also support the MJPEG format. If you choose this encoding format, during preview, only one channel of MJPEG encoding will be displayed. **Encoding Mode:** For simple scenarios, such as gray wall, set constant bit rate (CBR). For more complex scenarios, such as busy streets, variable bit rate (VBR) is appropriate.

Video Quality: Available only for VBR, this setting allows to select the recording quality,here are several options like **Lowest**, **Lower**, **Low**, **Medium**, **Higher**, **Highest**.


Config Mode: Select either User-defined mode to manually set the bitrate or Predefined mode to choose from predefined bitrate.

Bitrate: Determines the speed of data transfer used for video recording. Higher bitrates result in better-quality recordings but require more bandwidth. Adjust incrementally until satisfied with image qualit.

Audio: Enables or disables audio recording if your camera supports it. Make sure to enable Audio streaming in the Audio Encoding section if you want to record audio.

I Frame Interval: This parameter sets the interval between I frames (keyframes) in the IP camera's stream. I frames are full frames, while other frames are encoded based on the differences from preceding frames (P frames or B frames). A shorter interval can improve video quality but may increase bandwidth usage.

5.1.4.4 The third stream



Switch: Enable or disable the third stream.

Resolution: Determine the record to the third stream type. Higher values offer greater detail. The default resolution is auto-selected by your NVR.

Frame Rate: Specifies the number of frames recorded per second. The default frame rate is auto-selected by your NVR.

Encoding Format: Lists the supported codec for the connected camera. H.265 compresses. information more efficiently for better video quality at a given bandwidth. H.265+ offers even greater compression. H.264 requires higher bandwidth and offers less efficient compression. H.264+ provides additional compression compared to H.264. Please note that only some devices support H.264+ and H.265+. Please note that in the substream, some cameras also support the MJPEG format. If you choose this encoding format, during preview, only one channel of MJPEG encoding will be displayed.

Encoding Mode: For simple scenarios, such as gray wall, set constant bit rate (CBR). For more complex scenarios, such as busy streets, variable bit rate (VBR) is appropriate.

Video Quality: Available only for VBR, this setting allows to select the recording quality, here are several options like **Lowest**, **Lower**, **Low**, **Medium**, **Higher**, **Highest**.

Config Mode: Select either User-defined mode to manually set the bitrate or Predefined mode to choose from predefined bitrate.


Bitrate: Determines the speed of data transfer used for video recording. Higher bitrates result in better-quality recordings but require more bandwidth. Adjust incrementally until satisfied with image qualit.

Audio: Enables or disables audio recording if your camera supports it. Make sure to enable Audio streaming in the Audio Encoding section if you want to record audio.

I Frame Interval: This parameter sets the interval between I frames (keyframes) in the IP camera's stream. I frames are full frames, while other frames are encoded based on the differences from preceding frames (P frames or B frames). A shorter interval can improve video quality but may increase bandwidth usage.

5.1.4.5 Audio Encoding

If your camera includes a built-in microphone or an external audio input device, you can activate the audio stream. You can then adjust the input/output volume and select the audio encode type.



Enable: Tick to enable or disable audio.

Audio Input Type: This is to define the volume level of the audio output on the NVR locally.

Mic By Camera: Select the camera microphone input.


Line In: Select the camera audio line in.

Type: Choose the audio encoding codec, there are 711U and 711A.

Input Volume: Adjust the audio input volume. **Output Volume:** Adjust the audio output volume.

5.1.5 Image Capture

You can enable and schedule your NVR to capture snapshots during normal recording periods or whenever an event is triggered. This functionality aids in rapidly identifying alarm incidents and the snapshots can additionally be used for creating time-lapse video.




Auto Capture: Enable or disable snapshot capturing for this channel.

Normal Interval: The time interval between taking snapshots during regular recording periods. **Alarm Interval:** The interval for capturing snapshots when events like motion detection, I/O alarm. **Capture Resolution:** When the channel grasps, it can grasp according to the set resolution.

5.1.6 PTZ

This menu allows to configure the PTZ (Pan/Tilt/Zoom) settings for High-Speed dome.



Channel: Channel name.

Signal Type: If your PTZ camera is connected to the RS485 port, then choose "**Analog**", otherwise choose "**Digital**".

Protocol: Choose the communication protocol between the PTZ-enabled camera and the NVR. If the camera supports UTC (up coaxial) function, you can select COAX 1 or COAX 2 to display the camera's OSD menu or control UTC PTZ function.

Baudrate: The speed at which data is transmitted from the NVR to the PTZ camera. Ensure it matches the supported baud rate of your PTZ camera.

DataBit / StopBit: Data between the NVR and PTZ camera is sent in individual packets. The Data Bit indicates the number of bits in each data packet, while the Stop Bit signals the end of one packet and start of the next. Available Data Bit options are: 8, 7, 6, 5. Available Stop Bit options are 1 or 2. **Parity:** For error checking. Refer to your PTZ camera's documentation to configure this setting properly.

Address: Set the command address for the PTZ system. Note that each PTZ camera requires a unique address to function correctly.

Focus mode: There are three focus modes available.

- Auto: Automatically focuses based on scene changes.
- **Semi-auto:** Default mode. Focuses once after panning or zooming, and does not refocus with scene changes.
- Manual: The user manually focuses using the focus buttons on the preview interface. Panning, zooming, and scene changes do not trigger refocusing.

Zoom Status: The zoom status of the camera. The zoom level is displayed in the lower left corner of the preview interface. You can choose whether to display it or how long to display it.

Pan & Tilt Status: In the lower left corner of the preview screen, the horizontal and vertical azimuth of the camera will be displayed. You can choose whether or not to display it or how long to display it.

Preset Status: The preset status of the camera. The preset point number is displayed in the lower left corner of the preview interface when a preset is called. You can choose whether to display it or how long to display it.

Min. Focus Distance: When the distance between the scene object and the lens is less than the minimum focus distance, the lens will not change the focus on that object and will prioritize focusing on objects at distances greater than the "Minimum Focus Distance" parameter. For example, if the minimum focus distance is set to 6 meters, you can set a baffle at 1.5 meters to block part of the lens's field of view, with one half showing a distant view and the other a close view. The camera will prioritize focusing on the distant view beyond 6 meters.

5.1.6.1 High-Speed Dome Control

After completing the PTZ setting, the PTZ function can be used to control the High-Speed Dome camera.

Click the left mouse button in the live preview channel, tool bar at the bottom of the channel,

click

icon to enter PTZ control panel.



Channel: Select channel.

Mode: PTZ move control mode, there are six modes including PTZ, Preset, Line Scan, Watch Mode, Tour, Pattern Scan.


SPEED: The PTZ speed adjustment horizontal bar is divided into 1-10 gears, the larger the value, the faster the rotation speed.

Direction Control Buttons:





Clicking any of the 8 directional arrows will cause the camera's pan/tilt to make a slight movement in the corresponding direction.

Holding down one of the arrows will result in continuous rotation in that direction for the camera's pan/tilt. Clicking the center button initiates continuous horizontal rotation, and the button will



Represents "focus-" and "focus +". When pressing button, the lens pulls close and the scene enlarges. When pressing button, the lens pulls away and the scene becomes smaller.





Click to enable 3D positioning, and the button icon will turn blue; click the button again to stop 3D positioning. When the camera's 3D positioning is enabled, you can perform the following operations:


- Use the left mouse button to click on a specific point in the preview window, and the camera will move the clicked point to the center of the screen.
- Hold down the left mouse button and drag to the right to create a rectangular area, then release the
 button. The camera will move the outlined area to the center of the screen and zoom in for a closer
 view.
- Mold down the left mouse button and drag to the left to create a rectangular area, then release the
 button. The camera will move the outlined area to the center of the screen and zoom out for a wider
 view.
- click button, and the camera will automatically focus.
- One-Click Reset, click button, the camera will clear all preset points and cruise paths.

One-Click watch, click to perform a one-click watch, this function depends on the model, please refer to the actual interface.




PRESET mode:

Click icon, the preset points display below the preview screen, as shown in below picture.



Operating the cradle head controlled orientation key to turn

the cradle head to the location to be saved, click



preset points will be displayed in gray.

Click icon will rotate to the position set by the preset point, and take the shortest path.


frame, modify the preset point name. Click **Time** frame, modify the cruise time at this preset point.

Click 🛅

to delete the preset points.

Click on the Start Cruise to start cruising.

Note: Up to 255 preset points are supported.




Watch Mode: When the PTZ enabled watch mode function, after the set watch waiting time, no control signal comes, the PTZ dome will automatically perform the preset action.

Time Interval: Watch waiting time, the interval between the stop operation and the continue watch action.

Mode: Select watch mode, you can select Default Cruise, Preset Points Cruise, Line Scan, Track Cruise, Pattern Scan.

Click start the cruise.

Note: Only one watch point can be present.



Line Scan: Line Scan allows the camera to automatically pan horizontally between position A and position B.

Area scan: Click to record the start location, move PTZ and click to record the stop location.

Speed: Select the Line Scan cruise speed, here are Low, Medium, High.

Click to Line Scan cruise, The device will cruise at a constant speed between the start position and the end position.



Tour Cruise: You are able to configure a maximum of 4 tracks of automatic cruise sequences by selecting different preset points. To make full use of this Tour function, please ensure that several preset points have already been configured.

Track: Select track path.

Click + add preset points, click delete preset points.

Click start a cruise, and the device will cruise in the order of the preset bits added.

Note: After adding the preset point, you should click the cruise button to save the track path



Pattern Scan: Pattern scanning refers to the scanning according to the pre-set path, recording the horizontal and vertical movement, multiplier operation and other actions of the PTZ. After recording and saving, the pattern scanning route can be directly called. This function supports setting 4 pattern scan paths and provides saving options for each pattern scan path.

Track: Select track path.


Record: Click start recording cruise track, conduct an arbitrary PTZ operation on the device. Click to stop recording cruise track.

Click to cruise along previously recorded routes and movements.

5.1.6.2 PTZ schedule (This function only supports on mign-speed

Dome)

Click **Task Schedule** to set High-Speed Dome task schedule. The setting interface is shown in the following figure. User can set High-Speed Dome to automatically perform different cruise tasks in different time periods.




Enable: Enable or disable High-Speed Dome task schedule function. If the cruise times reach the limit, there will be a prompt on the right side of the switch.

Tasks Recovery Times (s): When High-Speed Dome performs the task according to the schedule, the manual operation interrupt cruise task, and after the task recovery time ends, the ball opportunity automatically recovers the cruise task corresponding to the schedule.

Task: Task type. The schedule task types of High-Speed Dome are closed, linear scan, trajectory cruise, pattern scan and preset points. The trajectory cruise and pattern scanning can both set 4 different paths respectively, and the preset point task can set the preset point with the number 1~8. **Note:** The task schedule has a higher priority than the Overwatch mode.

5.1.7 Video Cover

If the user wants to cover certain specific areas of the image screen, this feature will allow the user to create multiple privacy areas of any size and location. Enable the switch and select the privacy area required to enable. The area is displayed as the yellow box. Click the edge section of the yellow box and drag it to any size to create the privacy area.



Enable Video Cover: Enable or disable Video Cover function. When enabled, the set privacy area can be covered, and the covered area will not be seen in the preview and playback.

Polygon: Multiple privacy areas can be set in the screen, each area can be moved, stretch.

Click **Apply** to save and take effect.


Note: The video cover is set up, and the picture covered by the privacy area is not visible during preview and playback.

5.2 Storage

5.2.1 Schedule

5.2.1.1 Record schedule

This menu set when NVR records the video and determine the recording mode for each channel. The recording schedule sets up record schedule, such as **Normal** (continuous) daily (hourly) recording, **Motion** recording and **I/O** recording. To set the video mode, click (General, Motion, I/O) button and drag the cursor to mark the area or manually add the recording period in List form. The recording schedule is valid for only one channel. If you want to use the same recording schedule for another channels, click **Copy** to use the replication feature. Click **Save Template** to save the settings.



Channel: Select the channel to set video recording parameters.

Normal: Indicates the recording time period of normal video recording settings under the current channel.

Motion: Indicates the recording period of the motion detection video setting under the current channel.

I/O: The recording time period representing I/O alarm video settings in the current channel.

No Record: The time area marked as black in the table form indicates that no recording is scheduled for that session.




Table / List: The schedule table is presented in a table or a list form.

Select the Table form, drag or tick the corresponding time period in the table to set the corresponding time schedule.

Select the List form and set the corresponding time schedule by manually adding the rules and entering the start and end time periods.

Add: Add a schedule rule.

Delete All: Delete all schedule rules.

Start Time: Set the schedule rule start time.

End Time: Set the end time of the schedule rule.

Repeat: Set up the period during which the schedule rule takes effect.

Note: Up to 8 time periods are set. Each time period cannot be crossed or included.

Import Template: Import the custom or system default schedule template.


Edit: Edit the schedule template, you can modify the template name and the specific schedule rules.

Delete: Delete the schedule template.

Note: The system supports 7x24 and 5x24 schedule templates by default, which cannot be editable and deleted.

Save Template: Save the schedule template, you can save the currently set schedule rules as a custom template, which can be imported in the other schedule setting page.

5.2.1.2 Capture schedule



Channel: Select the channel to set its automatic capture parameters.

Normal: Indicates the time period under the current channel.

Motion: Indicates the time period of the motion detection and capture under the current channel.

I/O: Represents the time period when the I/O alarm capture under the current channel.


No Record: The time area marked as black in the table form indicates that no recording is scheduled for the record. Detailed settings refer to <u>5.2.1.1 Record Schedule.</u>

5.2.2 Storage

5.2.1 Hard Disk

This menu is used to manage and configure internal or external hard disk drives of the NVR, such as formatting disks, configuring record parameters and disk test.


Note: The models supporting four hard disk bits and above will display the Slot.NO bar, the information corresponding to the hardware SATA slot number.



Format HDD: Select the hard disk that needs to be formatted, click **Format HDD** button, and perform the formatting operation after checking the password from the pop-up menu.

NAS HDD: Support the configuration of network hard disk for recording and capture storage. You need to create a storage partition on the network hard disk in advance and successfully connect the network hard disk on the device through the network.

(Note: AI database, license plate database and video prompts file only is stored in local HDD drive.)



Mounting Type: Choose the mounting type from NFS and SMB/CIFS. You would need to input the account name and password of NAS if you choose SMB/CIFS.


- 8. User Name: Enter the NAS account name (In NFS mode, it is in an unselectable state)
- 9. Server IP: Enter the IP address of NAS storage.
- 10. Password: Enter the NAS password (In NFS mode, it is in an unselectable state)
- 11. Directory Name: Input the directory name on which you want to save your recording data.
- **12. Disk Size:** Set the capacity size of NAS storage.
- 13. **Test:** Click to test the connection to NAS storage.
- 14. Add NAS HDD: Click to add NAS storage.

Overwrite: This instructs your NVR to overwrite the oldest video files as the hard drive becomes full. You also have the option of selecting the amount of days for recordings to be kept before they are overwritten. For example, if you choose the option 7 days then only the last 7 days' recordings are kept on the HDD.

To prevent overwriting any old recordings, select **OFF**. If you have set Off on this feature, please check the HDD status regularly to make sure the HDD is not full. Recording will be stopped if HDD is full. We recommended leaving the **Auto** selection as this prevents your NVR from running out of storage space.

Record on ESATA: This menu only displayed when your NVR is coming with an E-SATA port on the rear panel and your E-SATA HDD has been connected to the NVR already. It will allow to record the video to external E-SATA HDD to enhance your HDD capacity. If the E-SATA recording function is enabled, E-SATA backup function will be disabled.

If your NVR supports to install multiple hard disks and more than 1 hard disk is installed in your NVR, the edit button will be appear in your system, you can click it to edit the HDD as below



Disk Type: You can set the hard disk to be Read Write, Read Only, or Redundant.


- Read Write type is the normal status for an HDD to save recordings or search recordings to play. If all the installed hard disks are set to Read Write mode, the NVR will save recordings to the hard disks sequentially.
- To prevent important video data from being overwritten during cyclic recording, the hard drive disk can be set as **Read Only** type. New recordings will not be able to be saved to this read-only disk. You can still search and play recordings from this read-only disk.
- A **Redundant** hard disk can be used to save the same recordings as what is saved to the Read Write hard disk(s). When a redundant disk is set, the system can save recordings in parallel to both the Read Write hard disk and the redundant hard disk in case of hard disk failure.

Note:

- 1. Redundant disk supports to save mainstream recording only.
- 2. If the disk type has been changed, the hard disks might be unmounted and offline. Please wait a while till the hard disks get mounted again.
- 3. For NVR with more than 32 channels, only Read Write and Read Only types are available **Disk Group:** You can set the disks into different disk group for recording.

5.2.2 Disk Group

If your NVR supports installing multiple hard disks, and more than one hard disk is already installed in your NVR, you will see this menu. With the Disk Group function, you can assign different cameras to different hard disks for recording, in order to reduce the loading on a single hard disk and extend the life of the hard disk. For example, record channels 1-16 to one disk group, and record channels 17-32 to another disk group.




- 1. On the disk list page, click on the edit button of the hard disk you want to configure, and then select its "Disk Type" and "Disk Group".
- 2. Go back to the "Disk Group" page, choose a Disk Group Type. If all the hard disks are set as Read Write mode, only Record Disk Group is available to choose here. If one or more hard disks are set as Redundant mode, Redundant Disk Group will be available to choose here.
- 3. Choose the "Disk Group".
- 4. Select the **Record Channel**. It indicates which camera(s) will be recorded and saved into the hard disk(s) in the selected group.

Click "Apply" to save your settings

Note: When the number of video channels configured by a single disk group exceeds 32, there may be a risk of video loss due to hard disk read and write performance. It is recommended that the number of video channels configured by a single disk group should not exceed 32.

5.2.3 S.M.A.R.T

This function can be used to detect and evaluate the running status of the hard disk in use, to detect risks in time and avoid data loss caused by hard disk failure.



Self-check Type: There are three types available.

Short: This test verifies major components of the hard drive such as read/write heads, electronics and internal memory.

Long: This is a longer test that verifies the above as well as performing a surface scan to reveal problematic areas (if any) and forces bad sector relocation.

Conveyance: This is a very quick test that verifies the mechanical parts of the hard drive are working. Note:

- 15. When performing a test, your NVR will continue to work as normal.
- **16**. If the hard disk S.M.A is found. R.T error, risk of missing recorded data, recommended to replace a new hard disk.


5.3 Alarm

This menu can configure series of alarm linkage made by the system to the alarm signals when various alarms are triggered.


5.3.1 I/O alarm

5.3.1.1 Alarm Input

This page display and configure the enabling situation of all I/O alarm input sources and a series of alarm linkages after triggering alarms.



Edit: Click button to open the configuration page, as shown in the below picture.



Alarm Input No.: Select the I/O alarm input source.

Type: Optional Normal-Open and Normal-Close, consistent with the type of access sensor.

Settings: With or not the I/O alarm input source.


Disable: Not enabled.

Input: Enable I/O alarm input, configure schedule and alarm linkage.

Post Recording: Set the duration of continuous NVR recording after the event occurs.

Schedule: Configure the time period of the current I/O alarm input source, and refer to 5.2.1.1

Record schedule.



Linkage: Configure a series of alarm linkage after triggering the alarm.

Buzzer: Set whether the device will beep after the I/O alarm occurs for 10 seconds.

Event Push platform: If the Event Push Platform switch is turned on, the camera sends a message to the third-party platform when the event alarm is triggered.

Show Message: Set whether the icon is displayed on the real-time preview channel after the I/O alarm occurs.

Email: Set whether to send an email to the mailbox after the I/O alarm occurs.

Risco Cloud Push: Set whether the device will push to the RISCO sever after the I/O alarm occurs.

Voice Prompts: Set whether to broadcast after I/O alarm occurs. Please refer to 5.3.4 Voice Prompts.

Alarm Output: Set whether the linkage alarm output after the I/O alarm occurs.

Channel Record: Set the channel to be recorded after the I/O alarm occurs.

PTZ Linkage: Set whether the PTZ is linked after I/O alarm occurs. (High-Speed dome requiring access support can be linked).

Preset: Linkage the preset point, set the residence time of the preset point and the When the I/O alarm occurs, the linkage to PTZ will rotate to the set preset point.


Tour: Set the track cruise and set the track. When the I/O alarm occurs, it will cruise according to the set track cruise linkage to PTZ.

Pattern Scan: Set the pattern scan. When the I/O alarm occurs, it will cruise according to the set pattern cruise linkage to PTZ.


Disarming: Enabled and Local <-1 is supported only. When enabled, Local <-1 is only used to control whether to perform one-key disarming. Detailed setting of disarming parameters can refer to **5.3.7 Disarming**.

5.3.1.2 Alarm Output

When event alarm triggered and linked to alarm output, the execution schedule and duration of the alarm output can be configured on this page.



Edit: Click button to open the configuration page, as shown in the below picture.



Alarm Output No.: Select the alarm output source.

Latch Time: Set the duration of the alarm output.

Alarm Status: Display the current I/O alarm output status.


Schedule: Configure the time period of the current alarm output source. Referring to the <u>5.2.1.1</u>

Record schedule.

Trigger: Set the manual alarm, click the button to open and close I/O alarm.

5.3.2 Exception

This menu can configure the alarm linkage for NVR exception events.



Event Type: There are 3 event types that your NVR will detect as exception.

HDD Full: The hard disk is full.

Disk Error: Hard drive error (While writing or hard drive is not initialized).

Video Loss: Video signal is lost (The channel is deleted or the channel is not correctly connected).

Switch: Enable or disable exception alarm.

Buzzer: When a detection event is triggered, you can enable the NVR's buzzer to provide an audible alert for a preset duration. Click the drop-down menu to select the desired time.

Alarm Out: If your NVR or IP camera supports connecting external alarm output devices, the system can send an alert notification to these devices.


Show Message: Set whether the icon or prompt language is displayed in the real-time preview interface after the event alarm occurs.

Email: Set whether to send an email to the mailbox after an event alarm occurs.

Voice Prompts: Set whether to broadcast after the event alarm occurs. Please, refer to <u>5.3.4 Voice Prompts</u>.

5.3.3 Combined Alarm

The Combined Alarm function allows to set combination of two or more alarm types at the same time. The NVR will only trigger alarm when all of specified alarm types in the combination occur simultaneously. It will help minimize false alarms.



Add Combined Alarm: Add a new set of combined alarms, and support up to 15 new groups.

Alarm Name: Set the name of the combined alarm.

Switch: Tick to enable the combined alarm.


Alarm Out: Set whether the alarm output is linked after the combined alarm occurs.

Record: Set the channel to be recorded after the combined alarm occurs.

Post Recording: Set the duration of continuous NVR recording after the combined alarm occurs.

Delete: Delete the combination of the alarm.

Nomal Linkage: Set up the routine alarm linkage after the combined alarm occurs, with the following options.



Buzzer: When detection event is triggered, you can enable the NVR's buzzer to provide an audible alarm for a preset duration. Click the drop-down menu to select the desired time.


Pop-Up: Set whether the window prompts automatically after the combined alarm occurs.

Email: Set whether to send an email to the mailbox after the combined alarm occurs.


Event Push platform: If the Event Push Platform switch is turned on, the camera sends a message to the third-party platform when the event alarm is triggered.

Risco Cloud Push: Set whether the device will push to the RISCO sever after the combined alarm occurs.

Voice Prompts: If your NVR is connected to a speaker, you can select a customized voice alert to play when a detection event triggers. See section <u>5.3.4 Voice Prompts</u> for adding custom voice file.



Don't show later: Tick this option do not automatically popup when trigger combined alarm. **Duration:** Set the continuous display time after the popup prompt. (**Note:** If the mouse is in the display area, the continuous display time will pause until the mouse moves out of the display area.) **Configuration:** Open the configuration page of the combined alarm.



Add: Add new combined alarm event.

Alarm Type: Select the alarm event type.

Alarm Source: Select the channel that supports the event type.


Delete: Delete the combined alarm event.

If the added combined alarm event is not enabled, there will be a red prompt after clicking **Apply** button. Click **settings** button to open the setting page of the alarm event.

5.3.4 Voice Prompts

This function is used for receiving the alarm and voice prompts device for linkage after the alarm occurs, and automatically or manually playing the audio related to the field "intrusion" behavior on the scene.

5.3.4.1 Voice File Management



Click **Import** to import audio file, support two kinds of audio import methods, including Import External File, Text-to-Speech (Internet).

Import External File: Local import (Support import MP3、WMA、WAV format of the audio file) . **Text-to-Speech(Internet):** Web server translation (Local import of text content that needs to be translated, sent to the network server to translate into audio files, and automatically save to the local hard disk storage) .

The text import box has a maximum input length of 200 bytes. **Import File:** Import audio files, The face database and license plate database allow each file size of 1~500K, Non-face database and license plate database allow each file size of 1~5M.

Import of the voice prompts audio is available in Voice File to select.


Voice Prompts support 2 kind of methods, Local and IP channels.

Local Audio Volume: Adjustable NVR local prompts volume output size.


IPC Sound Volume: Set the voice prompts volume output size of the camera channel. **Local:** Local broadcast (When selecting this mode of broadcasting, the device side should be connected to the audio output device) .

Channel: The IP camera broadcast (This choice of broadcasting mode requires the camera program to have a voice broadcast function, while the camera side supports audio output) .

Voice Prompts setting by time period: An alarm type can support a voice prompts for up to 12 time periods, with no conflict between the start and end time of any time period.




Voice prompts setting based on face recognition: this function is to realize the face recognition, the system collects the alarm signal and the voice broadcast equipment for linkage, and automatically plays the associated audio to the scene "intrusion" object. (**Note:** Audio imported based on face recognition allow and block list can only be used for the associated.).



That is, when trigger face detection will be voice prompt.

5.3.4.2 Loop Management




Voice File: After selecting the audio file and setting the time period, the selected audio file will be played repeatedly, and the voice broadcast can be set for up to 12 time periods.

Local: Local broadcast (when choosing this broadcast mode, the device side should be connected to the audio output device).

Channel: Network camera broadcast (choosing this broadcast mode requires the camera program with voice broadcast function, and the camera side supports audio output).

5.3.4.3IP Speaker

On this page, IP Speaker can be added and choose to broadcast to IP Speaker for voice prompts configuration.



Add IP Speaker: Press button to add IP Speaker.

Device Name: Set the name of the added IP Speaker.

IP Address: Enter IP address of the IP Speaker.

Port: Enter the port number for the IP Speaker.

Username: Enter the user name of the IP Speaker.

Password: Enter the IP Speaker password.

Bound Channel: Set the channel of IP Speaker binding.

Edit: Edit IP Speaker.


Delete: Edit button to delete IP Speaker.

Two-way Talk: Click button to match the device with the IP Speaker.

5.3.5 Deterrence

The menu can be configured with warming light, red and blue lights, and alarm deterrent parameters of camera channels(Access camera to support deterrence).

5.3.5.1 White light and Warning light



Channel: Select camera channel.

Light: Enable or disable white light.

Light Duration (s): Set the duration of the white light.

Light Mode: Set the white light mode, support Steady Mode and flicker mode Flashing Mode.

Flashing Frequency: The flashing frequency of the warming light, there are high, medium and low three levels are optional.


Warning Light: Enable or disable the red and blue light deterrent switch.

Warning Light Duration (s): Set the duration of red and blue light.

Schedule: For the installation of white light and red and blue lights, the schedule <u>5.2.1.1 Record Schdule</u>.

5.3.5.2 Siren

If the camera connected to the device has a built-in speaker, the parameters related to the alarm sound can be set.



Channel: Select the camera channel.

Enable: Toggle to enable or disable the siren function.

Siren Type: Used to select the siren audio file. Used to select the siren audio file. Depending on the model, the available alarm audio options may vary. Some models only allow you to select the built-in system alarm audio, while others allow you to upload up to three custom audio files. To use a custom audio file, select User-defined, and then upload the Pre-prepared audio file from a USB drive. The system supports importing PCM and WAV audio file formats. The imported audio file's sampling rate should not exceed 8000Hz, and the file size should not exceed 256KB. Once a custom audio file is selected, a Delete button will appear on the right side, allowing you to remove the current audio file.

File Name: Siren Type Select the User-defined option, Enter the file name and click on the right Import button select a custom audio file for importing the U disk.

Siren Level: Used to set the siren volume level, which ranges from 1 to 10. The higher the level is, the louder the volume is.

Siren Duration(s): Used to set the siren duration. You can adjust the value between 5 to 180 seconds.

Schedule: If the IP camera is connected to the NVR via the HTTP port, you can click the **Schedule** button to open the setting page.

Detailed information about Siren refer to 5.2.1.1 Record Schedule.


5.3.7 Disarming

Using the one-key disarming function, you can combine it with schedules to suppress alert behaviors for detected alarm events during specific time periods.

Note:

- 1. Exception alarm and Combined Alarm combined alarm linkage are not under disarming control.
- 2. One-click disarming enabled or disabled, it will not synchronize the disarming switch of the page.

- **3.** The one-click disarming function has the highest priority. After the one-click disarming is enabled, the disarming switch configuration status on the Disarming page will be ignored to ensure the immediacy of the one-click disarming commands.
- 4. Detailed information of disarming system refer to chapter <u>5.3.1.1Alarm Input</u>.



Disarming: Set to enable or disable the one-click disarming function.

Local: The NVR local alarm linkage type.

All: Select all types or empty all types.

Buzzer: Enable to disable the buzzer when an alarm is triggered while one-click disarming is enabled.

Alarm Out: Enable to disable external alarm output when an alarm is triggered while one-click disarming is enabled.

Email: Enable to prevent the NVR from automatically sending emails when an alarm is triggered while one-click disarming is enabled.

Full Screen: Enable to prevent channels configured for full-screen mode from entering full-screen on the preview screen when triggering an alarm while one-click disarming is enabled.

Voice Prompts: Enable to disable voice prompts on channels configured for voice prompts when an alarm is triggered while one-click disarming is enabled.

Privacy Mode: Enable disarming function, click **Privacy Mode**, the configured channel will disable the privacy mode.

Event Push platform: Enable to prevent the NVR from automatically sends a message to the third-party platform when an alarm is triggered while one-click disarming is enabled.


Risco Cloud Push: Enable to prevent the NVR from automatically pushing to the RISCO sever when an alarm is triggered while one-click disarming is enabled.

Camera: Camera alarm linkage type.

Audio and light alarm: Enabled disarming function, if the camera in the channel supports red and blue lights, white light and siren, red and blue light, warming light or siren won't response when trigger alarm.


Alarm I/O: Enabled disarming function, If the camera in the channel supports I/O alarm input /output. The I/O alarm input or output does not take effect.

Schedule: Configure the time periods when disarming is enabled. Detailed settings of the schedule table can be referred to <u>5.2.1.1 Record Schedule</u>.



5.4 Event


5.4.1 Event Settings



The user can easily enter the channel name of the camera through the input box to quickly locate the desired configured camera channel. Moreover, with the filter function button, the user can quickly screen all camera channels with this event type enabled.

5.4.1.1 Face detection

This menu allows to set parameters related to face detection.



Capture Mode: Snapshot mode, with **Optimal Mode** (From the appearance of the face to the disappearance, choose the best quality picture and push). **Real-time Mode** (push once when the face appears, push once again when it disappears) and **Interval mode** (custom push time and interval). **Snapshot Qty:** In interval mode, set the number of snapshots to push for each detection target in interval mode.

Capture Interval: Set the frequency of pushing snapshots of detection target in interval mode. **Face Angle:** Set the angle of detection, including Front View mode, Multi-angle mode and Userdefined angle mode.

- Front View: Only detects frontal/forward-facing faces.
- Multi-angle: Detects faces at multiple angles.
- **User-defined:** Customize the angle ranges for roll (rotation), pitch (vertical tilt), and yaw (horizontal pan) that faces should be detected.

Roll Angle: At User-defined mode, set the range of face rotation.

Pitch Angle: At User-defined mode, set the range of face pitch.

Yaw Angle: Set the range of face horizontal flip at custom angles.

Picture Quality: Set the image quality from 1 (lowest) to 100 (highest).

Frontal view/Multi-angle: Reset angle settings to defaults for frontal and multi-angle modes.

Min. Pixels: Set the minimum recognition pixel box, the face should be larger than the set pixel to be recognized.

Max. Pixels: Set the maximum recognition pixel box, the face should be smaller than the set pixel to be recognized.

Sensitivity: Set detection sensitivity level from 1-100. The larger the value, the easier it is to trigger. **Face Enhance:** Enhance for better recognition of moving faces, may lower overall picture quality. **Face Attributes:** After enabling this feature, the system will record the captured facial features, such as whether the person is wearing a mask or glasses, etc. Subsequently, when you search, you may be able to use these features to filter. This feature is only supported by some models, and due to product performance limitations, the recognized facial features may not be completely accurate.

Bounding Box: When enabled, a green bounding box will be displayed on the images, outlining and identifying detected targets. This aids in quickly locating and recognizing captured objects of interest. **Detection Mode:** This setting determines the method used to detect targets within the camera's field of view. There are two modes available, please choose according to your specific needs.

- Hybrid Mode: In this mode, both static and moving targets are detected. It combines detection of
 both stationary objects and those in motion. Hybrid mode is beneficial in scenarios where both
 static and moving objects may be of interest for surveillance.
- **Motion Mode:** This mode exclusively detects moving targets within the frame. It focuses solely on identifying objects in motion, ignoring stationary elements.

Trigger Mode: Used to set the area and path for triggering target detection, it allows you to customize the area or path that triggers detection, enabling the system to focus on the specific areas and movement paths you are concerned about.


Rectangle: In this mode, you can draw a rectangular area as the detection area. Any targets entering this area will be detected and trigger the corresponding alarms or actions.

Detection Area: For Rectangle mode, set the detection area. You can either select Full Screen detection, or choose User-defined to adjust the size of the quadrilateral detection area.

Rule Type: Under the Line mode, you need to draw a line inside the preview area, and set the crossing direction Rule Type (A->B or B->A) so that when a face crosses the line according to the set rule, it will be detected and trigger a response - suitable for scenarios requiring monitoring of targets crossing a certain path or boundary line.

5.4.1.2 Pedestrian and Vehicle detection

This menu allows you to set parameters related to detect pedestrian and vehicles.



Capture Mode: Used to set the method for capturing snapshots when a detection target is identified.

- Default Mode: Select the best quality picture to push during the time from when the detection target appears to when it disappears.
- **Real-time Mode:** Push once when the detection target appears and again when it disappears. **Snap Qty:** In the interval mode, Set the number of snapshots to push for each detection target in interval mode.

Capture Interval: Set the frequency of pushing snapshots of detection target in interval mode. **Min. pixels:** Set the minimum identification pixel box, the person and vehicle should be larger than the set pixel to be identified.

Max. Pixels: Set the maximum recognition pixel box, the person and vehicle should be smaller than the set pixel to be identified.

Sensitivity: Set the sensitivity level, ranging from 1 to 100. The higher the value, the more easily it will be triggered.

Detection Target: Choose the detection target object. You can select from Pedestrian, Motor Vehicle, and Non-motorized Vehicle.


Detection Mode: This setting determines the method used to detect targets within the camera's field of view. There are two modes available, please choose according to your specific needs.

- Hybrid Mode: In this mode, both static and moving targets are detected. It combines detection of
 both stationary objects and those in motion. Hybrid mode is beneficial in scenarios where both
 static and moving objects may be of interest for surveillance.
- **Motion Mode:** This mode exclusively detects moving targets within the frame. It focuses solely on identifying objects in motion, ignoring stationary elements.

Bounding Box: When enabled, a green bounding box will be displayed on the images, outlining and identifying detected targets. This aids in quickly locating and recognizing captured objects of interest. **Detection Area:** Used to set the area for triggering target detection, it allows you to customize the area, enabling the system to focus on the specific areas you are concerned about. You can either select Full Screen detection, or choose User-defined to adjust the size of the quadrilateral detection area.

5.4.1.3 License Plate Detection

The License Plate detection function utilizes video analytics to detect and recognize the license plates of vehicles passing through the camera's field of view. In the License Plate menu, you can configure various parameters related to this detection function.



Min. pixels: Minimum recognition pixel box, the license plate must be bigger than the set minimum pixel to be recognized.

Max. pixels: Maximum recognition pixel box, the license plate should be smaller than the set maximum pixel to be recognized.

Detection Target: Select the type of license plate, such as American license plates, European license plates, etc.

Detection Mode: This setting determines the method used to detect targets within the camera's field of view. There are two modes available, please choose according to your specific needs.

- European license plate: European license plate.
- American license plate: American license plate.

Select Mode: Application mode, according to the actual installation position to select the corresponding application mode can improve the effect of license plate capture, there are the following three modes.

Entrance / Exit: Gate entrance and exit scene.

City Street: City street scene.

Alarm Input: Alarm input mode (the camera is required to support I/O alarm input).

Note: Select **Entrance/Exit** and **City Street** need to set detect line position in the video screen. When the license plate touches the detection line will capture. Select Alarm Input mode, don't need to set up detection line, when the alarm input is triggered, the license plate in the detection area will always be captured until the alarm input signal is over.

Detection Area: Used to set the area for triggering target detection,, it allows you to customize the area, enabling the system to focus on the specific areas you are concerned about:

Full Screen: Detect the full screen area


User-defined: Customize the detection area.

Bounding Box: When enabled, a green bounding box will be displayed on the images, outlining and identifying detected targets. This aids in quickly locating and recognizing captured objects of interest. **LPD Enhance:** Enable/disable license plate enhancement. License Plate Enhance is a feature that helps improve the clarity and readability of license plates in the captured images or video feed. Its main purpose is to enhance the license plate region, making it easier for the license plate detection algorithms to accurately recognize and identify the license plate characters.

Note: Enabled the LPD Enhance, the image control automatically switch to day and night mode, IR-CUT Mode will switch to Image mode and hide Exposure Compensation, Shutter and Exposure Time.

5.4.1.4 Intrusion

Intrusion detection can detect whether there is an object invading the set restricted area in the video. This feature is useful for monitoring restricted areas and detecting unauthorized entry or trespassing activities. It helps enhance security and surveillance in locations such as warehouses, construction sites, or other restricted premises. Whether this feature is supported depends on the camera model being used.



Loitering Duration: It indicates the time duration (in seconds) an object must remain in the alert area before triggering an alarm. For example, if set to 5, the alarm will trigger immediately after the target has invaded the area for 5 seconds. The maximum duration can be set up to 10 seconds.

Target Validity: Target confidence, indicating the similarity between the target and the set detection type, and the alarm will be triggered only after reaching or exceeding the set similarity. The higher the setting level, the higher the similarity requirement, the more obvious the required target features, and the higher the alarm accuracy. Level can be set to 1 to 4,1 as the highest confidence. The similarity requirements of the detection target corresponding to each level are: 1~80%, 2~60%, 3~40%, and 4~20%.

Min. Pixels: Set the minimum recognition pixel, the target should be bigger than the set pixel to be identified.

Max. Pixels: Set the maximum recognition pixel, and the target should be smaller than the set pixel to be identified.

Sensitivity: Sensitivity setting to trigger area intrusion detection, the higher the sensitivity setting, the easier it is to trigger the alarm.

Detection Target: Set the target type that needs to be detected.

- **Pedestrian**: Only detect intruding pedestrians
- Motor Vehicle: Only detect intruding motorized vehicles
- **Non-Motorized:** Only detect intruding non-motorized vehicles

No Target Type Selected: All moving targets will be detected.


Rule Number: Select the rule number. In the upper preview screen, click the left mouse button to draw the detection area connected by the head and tail end points. After drawing, click Save to complete the area drawing. When the alert area needs to be cleared, click "Remove to delete the selected painted area. Click "Remove All " to delete all painted areas.

Rule Switch: When enabled, the set detection area takes effect.

Bounding Box: When enabled, the target detection frame displays in the real-time screen.

5.4.1.5 Enter Region

The Enter Region Detection function can detect whether target enters the set alert area, and link the alarm according to the judgment result.



Target Validity: Target confidence, indicating the similarity between the target and the set detection type, and the alarm will be triggered only after reaching or exceeding the set similarity. The higher the setting level, the higher the similarity requirement, the more obvious the required target features, and the higher the alarm accuracy. Level can be set to 1 to 4,1 as the highest confidence. The similarity requirements of the detection target corresponding to each level are: 1~80%, 2~60%, 3~40%, and 4~20%.

Min. Pixels: Set the minimum recognition pixel, the target should be greater than the set pixel to be identified.

Max. Pixels: Set the maximum recognition pixel, and the target should be smaller than the set pixel to be identified.

Sensitivity: trigger the sensitivity setting of area intrusion detection. The greater the sensitivity setting, the easier it is to trigger the alarm.

Detection Target: Set the detection target, can choose "human type", "motor vehicle", "non-motor vehicle". "Human type" means only invading pedestrians, "motor vehicle" means only invading motor vehicles, "non-motor vehicle" means only invading non-motor vehicles, and "no type" means detecting all moving targets.


Rule Number: Select the rule number, click the left mouse button in the top preview screen to draw the detection area connected by the end and tail ends. After the drawing, click Save to complete the area drawing. When the alert area needs to be cleared, click ". Remove to delete the selected painted area. Click ". Remove All ". to delete all painted areas.

Rule Switch: When enabled, the set detection area takes effect.

Bounding Box: When turned on, the target detection frame is displayed in the real-time screen.

5.4.1.6 Exit Region

The Exit Region function can detect whether there is an object leaving the set alert area, and link the alarm according to the judgment result.



Target Validity: Target confidence, indicating the similarity between the target and the set detection type, and the alarm will be triggered only after reaching or exceeding the set similarity. The higher the setting level, the higher the similarity requirement, the more obvious the required target features, and the higher the alarm accuracy. Level can be set to 1 to 4,1 as the highest confidence. The similarity requirements of the detection target corresponding to each level are: 1~80%, 2~60%, 3~40%, and 4~20%.

Min. Pixels: Set the minimum recognition pixel, the target should be greater than the set pixel to be identified

Max. Pixels: Set the maximum recognition pixel, and the target should be smaller than the set pixel to be identified.

Sensitivity: trigger the sensitivity setting of area intrusion detection. The greater the sensitivity setting, the easier it is to trigger the alarm.

Detection Target: Set the detection target, can choose "human type", "motor vehicle", "non-motor vehicle". "Human type" means only invading pedestrians, "motor vehicle" means only invading motor vehicles, "non-motor vehicle" means only invading non-motor vehicles, and "no type" means detecting all moving targets.


Rule Number: Select the rule number, click the left mouse button in the top preview screen to draw the detection area connected by the end and tail ends. After the drawing, click Save to complete the area drawing. When the alert area needs to be cleared, click ". Remove to delete the selected painted area. Click ". Remove All ". to delete all painted areas.

Rule Switch: When enabled, the set detection area takes effect.

Bounding Box: When turned on, the target detection frame is displayed in the real-time screen.

5.4.1.7 Line Crossing

The Line Crossing function can detect people, vehicles or other objects that have crossed a predetermined virtual line and take certain measures when an alarm is triggered.



Target Validity: Target confidence, indicating the similarity between the target and the set detection type, and the alarm will be triggered only after reaching or exceeding the set similarity. The higher the setting level, the higher the similarity requirement, the more obvious the required target features, and the higher the alarm accuracy. Level can be set to 1 to 4,1 as the highest confidence. The similarity requirements of the detection target corresponding to each level are: 1~80%, 2~60%, 3~40%, and 4~20%. **Min. Pixels:** Set the minimum recognition pixel, the target should be greater than the set pixel to be identified.

Max. Pixels: Set the maximum recognition pixel, and the target should be smaller than the set pixel to be identified.

Sensitivity: trigger the sensitivity setting of Line Crossing. The greater the sensitivity setting, the easier it is to trigger the alarm.

Detection Target: Set the detection target, can choose "human type", "motor vehicle", "non-motor vehicle". "Human type" means only invading pedestrians, "motor vehicle" means only invading motor vehicles, "non-motor vehicle" means only invading non-motor vehicles, and "no type" means detecting all moving targets.

Rule Number: Select the rule number, click the left mouse button to draw the appropriate detection line in the top preview screen. After the drawing, click Save to complete the detection line drawing. When the detection line needs to be cleared, click "Remove to delete the selected detection line. click" Remove All " to delete all detection lines.

Rule Switch: When enabled, the set detection line takes effect.

Rule Type: Select the rule type

A (B: detect only the movements from side A to side B.

B (A: detect only the movements from side B to side A.

A ((B: will detect movements from side B to side A or from side A to side B.


Bounding Box: When turned on, the target detection frame is displayed in the real-time screen. Notes:

- 1. The detection line should not be too close to the edge of the camera image, so as to trigger an alarm when the target passes through the camera.
- **2.** The detection line should not be set too short to avoid failing to trigger an alarm when the target crosses the detection line.



5.4.1.8 Object Detection

The Object detection can detect the objects left or lost in the predetermined area, such as luggage, wallet, dangerous goods, etc., and take a series of measures when triggering the alarm.



Sensitivity: Sensitivity, parameter range of 1 to 4, default value of 2. The higher the sensitivity, the more likely the left or lost objects in the detection area will be detected, and the more false detection will be detected, and the corresponding missed detection will be reduced. It is recommended to keep the default value.

Rule Number: Select the rule number, click the left mouse button in the top preview screen to draw the detection area connected by the end and tail ends. After the drawing, click Save to complete the area drawing. When the alert area needs to be cleared, click ". Remove to delete the selected painted area. Click ". Remove All ". to delete all painted areas.

Rule Switch: When enabled, the set detection area takes effect.

Bounding Box: When turned on, the target detection frame is displayed in the real-time screen.

Rule Type: Select the rule type.

Legacy: Detect only the objects left in the detection area.

Lost: only detect lost objects in the detection area.

Lost & legacy: will detect left and lost objects in the detection area.

Mouse-click 4 points in the camera image to draw a virtual area. The area shall be a convex polygon. The concave polygon will not be saved.


Note:

- 1. The detection area should be greater than or equal to the size of the detected object, such as the detection of blue bottles.
- 2. The detected objects cannot be obscured.



5.4.1.9 Cross Counting

The Cross Counting function counts the statistics of people, motor vehicles, non-motor vehicles or moving objects that cross the detection line.



Sensitive: The sensitivity level is 1 to 4, and the default value is 2. Higher sensitivity will trigger detection more easily.

Detection Target: Set line crossing statistics target type

Motion: Count any moving objects over the line.

Pedestrian: Only count the pedestrians crossing the line.

Motor Vehicle: Only count the motor vehicles that cross the line.

Non-motorized Vehicle: count only the non-motor vehicles passing the line.

Alarm Number: Set the number of alarms. Alarm Num= (number of cross in) - (number of cross out), reaching the set value will alarm.

Reset Count: Clear the count and recount.

Rule Switch: When enabled, the set detection line takes effect.

Rule Type: Rule type

A-> B: People or objects from side A to side B will be counted.

B-> A: People or objects from side B to side A will be counted.

Bounding Box: When turned on, the target detection frame is displayed in the real-time screen.

- 1. Click the "Add d (Add)" button to add a detection line or click the "Draw (Draw)" button to manually draw a detection line. If you want to modify the position or range of the detection line, click the red box in the line and the color of the line turns red. Long press the left mouse button to move the detection line, or drag the endpoint to modify the length or position of the line.
- **2.** If you want to delete the detection line, click the red box in the line, and then click the Remove (Remove) button.

Notes:

- 1. The detection line should not be too close to the edge of the image to avoid not triggering the alarm when the target crosses the detection line.
- 2. The test line should be located in the area where the detected object can reach.
- 3. The detection line should not be set too short so as not to trigger the alarm when the target crosses the detection line.



5.4.1.10 Heat map

Show the diagram of the page area of the visitor and the geographical area of the visitor in a special highlight form, and the heat map also shows which areas of the picture attract most of the visitors.




Rule Switch: Enable or disable the detection area.

Add: Add a default detection region. **Draw:** manually draw the detection area.

Remove: Select the detection area box and click Remove to remove the detection box.

5.4.1.11 Crowd Density

Crowd Density function is used to detect population aggregation to maintain a controllable order in a specific area.



Min. pixels: Set the minimum recognition pixel box, the person should be greater than the set pixel to be identified.

Max. pixels: Set the maximum recognition pixel box, the person should be less than the set pixel to be identified.

Sensitivity: Sensitivity levels are from 1 to 4. Higher sensitivity would trigger detection more easily. **Max Detection:** When the number of people in the detection area exceeds the maximum number, the population density alarm will be triggered.

Bounding Box: When turned on, the target detection frame is displayed in the real-time screen.

Detection Area: Test areas for population density are set, as follows:

Full Screen: Full-screen detection. **User-defined:** Custom test area.

Rule Switch: Enable or disable the detection area.

5.4.1.12 Queue Length

Queue Length detection is used to detect the status of the cohort, including its length and stall time.



Min. pixels: Set the minimum recognition pixel box, the person should be greater than the set pixel to be identified.

Max. pixels: Set the maximum recognition pixel box, the person should be less than the set pixel to be identified.

Sensitivity: Sensitivity levels are from 1 to 4. Higher sensitivity would trigger detection more easily. **Max Detection:** When the number of people in the detection area exceeds the maximum number of people, the queue length alarm will be triggered.

Max. Staying Time: When the stop time of the queue exceeds the set processing time, the queue length alarm will be triggered.

Bounding Box: When turned on, the target detection frame is displayed in the real-time screen.


Detection Area: Set the detection area of the queue length in the following two types:

Full Screen: Full-screen detection.

User-defined: Custom test area.

Rule Switch: Enable or disable the detection area.

5.4.1.13 Rare Sound



Sensitivity: Sensitivity setting, higher sensitivity will be easier to trigger detection.

Detection Target: Detection type


Baby Crying: Baby crying can be detected after checking.

Dog Barking: The barking sound can be detected after checking.

Gunshot: Gunfire can be detected after checking it.

5.4.1.14 Motion Detection

Users can configure the relevant parameters for the motion detection on this page. A motion detection alarm is triggered when the motion target in the screen.



Sensitivity: Set the sensitivity level, the higher the sensitivity, the farther the distance of detection. SMD by Recorder: Suitable for cameras that do not support intelligent motion detection function, with Pedestrian, Vehicle, and two detection types are optional. Without checked, the movement of any object can trigger a motion detection alarm.

SMD by Camera: Suitable for network cameras to support intelligent motion detection function, Pedestrian, Vehicle, two detection types are optional. Without checked, the movement of any object can trigger a motion detection alarm.

5.4.1.15 Video Tampering


The Video Tampering function can be used to detect whether the monitoring picture is blocked and to take a series of measures when the alarm is triggered.



Sensitivity: The sensitivity level is 1 to 6, and the default value is 4. The higher the sensitivity, the easier it is to trigger the alarm.

5.4.1.16 Schedule sheet

Configure the time period for each event, and the schedule details refer to 5.2.1.1 record schedule.




Note:

- 1. Setting schedule is not supported for heat map.
- 2. The camera channel move detection is not supported by the Onvif protocol.

5.4.1.17 Alarm linkage

After configure the alarm trigger of each event, execute the corresponding alarm linkage.



Buzzer: Set whether the device will beep after the event alarm occurs, and the beep lasts for 10 seconds.

Event Push platform: If the Event Push Platform switch is turned on, the camera sends a message to the third-party platform when the event alarm is triggered.

Full Screen: Set whether the full-screen preview of the channel after the event alarm occurs. **Show Message:** Set whether the icon is displayed on the real-time preview channel after the event alarm occurs.

Risco Cloud Push: Set whether the device will push to the RISCO sever after an event alarm occurs. **Email:** Set whether to send an email to the mailbox after an event alarm occurs. Click the setting button and schedule button on the right to configure the message parameters. Please refer to <u>5.5.4.1</u> <u>email configuration</u> for detailed settings.

Picture Upload: Set whether to upload the alarm grab map to the configured FTP server and cloud storage server after the event alarm occurs.

Video Upload: Set whether to upload the alarm video to the configured FTP server and cloud storage server after the event alarm occurs.

I/O Output: Set whether the alarm output after the event alarm occurs. Click the setting button on the right to configure the alarm output source.

PTZ Linkage: Set whether the PTZ is linked after the event alarm occurs. Click the right setting button to configure the PTZ linkage. (High-Speed Dome requiring access support can be linked)

Preset: Linkage the preset point, set the residence time of the preset point and the preset point. When the event alarm occurs, the linkage PTZ will rotate to the set preset point.

Tour: Set the track cruise and set the track. When the event alarm occurs, it will cruise according to the set track cruise linkage PTZ.

Pattern Scan: Set the pattern scan. When the event alarm occurs, it will cruise according to the set pattern cruise linkage PTZ.

Deterrence: Set whether the warm light and red and blue light of the camera are linked after the event alarm occurs. Click the setting button on the right side to configure the Deterrence parameters of the camera. Please refer to 5.3.5.1 warm light and red and blue light for detailed setting.

Siren: Set whether to link the alarm sound of the camera after the event alarm occurs. Click the setting button on the right side to configure the Siren parameters of the camera. Please refer to <u>5.3.5.2 siren</u> for detailed setting.

Voice Prompts: Set whether to broadcast after the event alarm occurs. Please, refer to <u>5.3.4 Voice Prompts</u>.

Recording Channel: Set the channel required to record after the event alarm occurs. **Recording Delay:** Set the duration of continuous recording after the event alarm occurs.

5.4.2 List Management

5.4.2.1 Face Recognition Management


This menu can set the database and alarm linkage.



Import Database: The exported face data can be imported into the device.

Backup Database: You can export the face database to the U disk.

Update face attributes: Update face features, in switching the face feature model or imported face images or face library, from the camera recognition to detect the face after the face library face image face features and the current check face features model is inconsistent, will pop up update face features, click update face features will be shown in the following figure.




Click Cancel will prompt to continue or stop the update, the remaining not updated next click to update


Click :You can add new face groups or delete existing face groups. (The default first three face groups cannot be deleted)

Enable: The face group can be enabled or closed.


Edit: Click Edit to enter the Edit face group interface.



Import: Click and select Local Storage Device to add the local face interface.




Select the date, duration and channel after point Search to search for faces saved by all devices during that time. If the face is set similarity and then click Search, you will search out the face matching the selected face similarity. Select the face in the search area and click Delete to delete the face in this search area. Select the human face and click OK to enter the input human face information interface



On the right side, the face information can edit the information. After editing, click Import to complete the import and click Exit to exit the interface.


Click **External Storage Device** to enter the external memory, select the face picture you want to import, the same step as importing the local face.



Export: Export the face image to the external memory, if not click to the face group image to click Export to export all the face group face image. If click to the face group face image to click Export to export the selected face image.

Download import Template: Download and import the template, can export a template to external memory, this template can contain a table and instructions, can fill in the face picture information in this form, import this form can modify the information of multiple face pictures, convenient to modify the face picture information.

Right click to select the face picture, select Edit to enter the face picture editing interface, click **Additional Face Images** to import the face picture in different circumstances of the face.




Alarm: Open or close the face comparison alarm of the face group.

Policy: Set up the face group alarm countermeasures

Similarity: Similarity setting

Alarm Linkage: Click to enter the setting interface.



Buzzer: Set whether the device sounds beep after the alarm, and the beep lasts for 10 seconds. **Alarm Out:** Set whether the alarm output is linked after the face comparison alarm occurs. Click the setting button to configure the alarm output source.

Email: Set whether to send an email to the mailbox after the face comparison alarm occurs. **FTP Picture Upload:** Set whether to upload the alarm grab to the configured FTP server after the alarm occurs.

Picture to Cloud: Set whether to upload the alarm grab to the configured cloud storage server after the alarm occurs.

Event Push platform: Set whether the device will send a message to the third-party platform after the alarm occurs.


Voice Prompts: Set whether to broadcast after the face comparison occurs. Please refer to <u>5.3.4 Voice</u> **Prompts.**

Alarm Schedule: Set the time period for each camera channel to enable face alignment. Please refer to <u>5.2.1.1 Record schedule</u>.

Alarm Channel: Set the channel for the face group to enable the face comparison and alarm.

5.4.2.2 License Plate Management

This menu can set the database of the license plate identification comparison and the alarm linkage.



Import Database: You can import the exported group data into the device.


Backup Database: You can export all the groups to the U disk.

Group Name: The name of the database group, expressed as a white list, expressed as a blacklist, indicating the unfamiliar license plate list, at the same time, you can add up to 61 custom groups, a total of 64 groups, one group can accommodate up to 5,000 license plate information, the whole database can accommodate 10,000 license plate information.

Click You can add a new plate group or delete an existing plate group. (The first three plates cannot be deleted)

Enable: The license plate group can be enabled or closed.


Edit: Click Edit to enter the edit license plate group interface.



Search: License plate can be filtered according to keywords.


Total: Total number of license plate data in this group.

Click to modify the corresponding license plate data information.



There are three ways to add license plate information: Import, Import From CSV and Import From Local .

Click Import button to manually add a single license plate information.




Click **Export** button to export the entire group information to the external U disk.


Alarm Channel: Set the channel to alarm after the license plate is detected and compared successfully. **Move to...:** Check the check box of the license plate information and then click this button to transfer the license plate information to another group.

Delete: Check the check box of the license plate information and then click this button to delete the license plate information.

Click Import From CSV button to import a single piece or multiple pieces of data into the CVS table.




Click **Import From CSV** button to pop up the above interface, select the license plate file of CSV that needs to be imported, and click the OK button. The interface as shown as below picture.



Click **Import/Modify** button to add the batch, or you can also select a single license plate information to modify it. When more than 5000 data are added, the message box appears as shown in the figure above, and the content is "the added data has reached the upper limit of the group".


Click Import From Local button to import the license plate information locally to the database.



Select the date, duration and channel back point Search to search for the license plates saved by all the devices during this period.

Channels: License plate detection events triggered by each channel can be searched.

Select All: Select all the license plate information.




Click a piece of data to edit the license plate information. After editing, click the Import / Modify button to modify it, if the modification is successful. Will become.

Alarm: Open or close the license plate comparison alarm.

Policy: Set up the license plate group alarm countermeasures.

Fault-tolerant: Fault tolerance character. For example, when set to three characters, the license number of the white list in the group is B594SB, and when the license number of B734KB enters the monitoring area, an alarm is also triggered. That is, the detection license plate number has 0~5 characters and the database license plate number is different will alarm.

Alarm: Click to enter the setting interface.



Buzzer: Set whether the device emits a beep after the alarm occurs, and the beep lasts for 10 seconds. **Alarm Out:** Set whether the alarm output is linked after the alarm occurs. Click the setting button to configure the alarm output source.

Email: Set whether to send an email to the mailbox after the alarm occurs.

FTP Picture Upload: Set whether to upload the alarm grab map to the configured FTP server after the license plate comparison alarm occurs.

Picture to Cloud: Set whether to upload the alarm grab map to the configured cloud storage server after the license plate comparison alarm occurs.

Event Push platform: Set whether the device will send a message to the third-party platform after the alarm occurs.


Voice Prompts: Set whether to broadcast by voice after the license plate comparison occurs. Detailed setting can refer to <u>5.3.4 voice prompts</u>.

Alarm Schedule: Set the time period for each camera channel to enable license plate alignment. Referring to <u>5.2.1.1 Record schedule</u>.

Alarm Channel: Set the channel for the license plate group to enable the license plate comparison alarm.

5.4.2.4 Analysis and configuration of personnel frequency

The device supports the personnel frequency analysis function, which can automatically monitor and count the occurrence frequency of personnel in the designated monitoring area, providing data support for the people flow analysis scene.



Channel: Check the channel for personnel frequency analysis, and the personnel identified on the failed channel will not be included in the statistics.

Groups...: Check the face list group for personnel frequency analysis.

Check Interval (min): Frequency interval time, set the interval time between two adjacent appearances of the same person. If the same person is identified multiple times during the frequency interval, the frequency count of the person will not increase.

Similarity: Similarity setting, the identified person and the count statistics of the person after meeting the threshold.

Max Stranger Count: The device supports the maximum number of strangers counted.

Alarming: Personnel frequency alarm switch, send alarm when the personnel frequency reaches the preset frequency threshold.

Filter Out Alarms for Age Under: Minor alarm filtering, When the age of the identified person is lower than the set age, filter the person without alarm.

Alarm Frequency Threshold: Warning frequency threshold.

Alarm Statistical Period (Day): alarm statistics period, only the frequency of personnel in the preset period.


Buzzer: Set whether the equipment will beep after the personnel frequency alarm occurs for 10 seconds.

I/O Output: Set whether the alarm output after the frequency alarm occurs. Click the right setting button to configure the alarm output source.

Voice Prompts: Set whether to broadcast after the personnel frequency alarm. Reference to <u>5.3.4 Voice Prompts</u>.

5.4.2.4 Model configuration

This menu can configure the face recognition model, support the selection of NVR local model or camera model.



5.4.3 Statistical analysis

5.4.3.1 Face recognition statistics

In the face recognition statistics, the statistics can be made on all the faces detected in a period of time, and reflected in the way of a statistical chart.




After selecting Groups, Channels, date, and statistical time, the statistical results will be given directly out. Click **Export** to import the data to the U disk.

Face Search: Click the face search button to jump directly to the intelligent playback face search page. **Repeat Visitors:** Click the face statistics button to jump directly to the intelligent replay repeat customer page.

Face Attendance: Click the face attendance button to jump directly to the intelligent playback face attendance page.

5.4.3.2 Pedestrian and Vehicle Statistics

In the pedestrian and vehicle statistics, all of detected pedestrian and vehicle that appear in a period of time can be counted and reflected in the form of statistical charts.




After selecting the type, Channels, date and statistical time in the AI, the statistical results will be given directly out.

Pedestrian and Vehicle Search: Click Pedestrian & Vehicle button to jump directly to the intelligent playback pedestrian & Vehicle page.

5.4.3.3 Cross Counting Statistics

In crossing counting statistics, the number of times in and out of a period of time can be counted, and reflected in the way of statistical chart.



Channel: Select the channel that you want to search.

Date: Select the date that you want to search.

Report Type: Select the report type, including Daily Report, Weekly Report, Monthly Report, and Annual Report four types of report.

Cross Type: There are two types of penetration: Cross-line Enter and Cross-line Exit.

Detection Target: Select the detection type that triggers the Cross Counting, with four options:

Motion, Person, Motor Vehicle, and Non-motorized Vehicle.

Click Search button to query for data.


Export: Results to export the external U disk.

Column Chart: Select the bar chart to display.

Line Chart: Select the line diagram to display.

5.4.3.4 Heat Map Statistics

In the heat map statistics, the frequent activity of some areas during a period of time can be counted and reflected in the way of statistical map.



Channel: Select the channel that you want to search for.

Date: Select the date that you want to search.

Start Time: Select the start time. **End Time:** Select the end time.

Report Type: Select the report type, including Daily Report, Weekly Report, Monthly Report, and

Annual Report four types of report. Click **Search** button to search for data

Export: Results to export the external U disk.

Spatial Heatmap: Select the spatial distribution map to display.

Time Heatmap: The selection time distribution diagram is shown.


The selection time distribution map has no choice of Start Hour and End Hour.

Spatial density legend: Comparison of spatial density levels.

5.5 Network

5.5.1 General

5.5.1.1 General Configuration



If the network connected to the device has a DHCP service, check the DHCP box, and the DHCP service will automatically assign all network parameters to the device. or manually set the following network parameters:

IP Address: IPV 4 address is the identity of NVR in the network. It consists of four sets of numbers between 0 and 255, separated by periods. For example, "192.168.001.100".

Subnet Mask: A subnet mask is a network parameter that defines the range of IPV 4 addresses that can be used in the network. Subnet addresses also consisted of four sets of numbers, separated by periods. For example, "255.255.000.000"

Gateway: The IPV 4 gateway address of the network where the device is located, the default is: 192.168.001.001.

IPv6 Address: The IPv6 address is the identity of the NVR in the network. It consists of eight sets of numbers between 0 and FFFF, separated by colons. For example, "ABCD: EF01:2345:6789: ABCD: EF01:2345:6789".

IPv6 Gateway: The IPV 6 gateway address of the network where the device is located.


DNS 1 / DNS 2: DNS 1 is the primary DNS server, and DNS 2 is the standby DNS server. Usually just enough to enter the DNS 1 server address.

Web Compatibility Mode: If the selected browser does not support web-side access to the device, please enable web compatibility mode. Compatible mode will choose the insecure encryption algorithm, please choose carefully.

Channels...: Set the channel to the client to encrypt the transmission video stream.

POE DHCP Server: IP address allocation for the camera connected by the PoE port. (Note: This option is shown with only POE)

5.5.1.2 PPPoE




PPPoE networking is enabled, and devices can connect to the network through dial-up Internet access. Select the Enable PPPoE box and enter the user name and password (the user name and password are available from the carrier).

Click **Apply** to save, and the system restart will automatically dial the number. After successful dialing, the network information can be displayed on this page.

5.5.1.3 SNMP


The user can obtain the device parameters and receive the device through the SNMP protocol.



Notes:

- 1. Before setting SNMP parameters, users need to download SNMP software and receive the information of the device through the SNMP port, such as software version number, device type, channel IP, resolution, frame number, etc.
- 2. Set the Tap management address, and the device can send alarm and abnormal information to the management station.


5.5.1.4 Wireless Configuration



After the device is connected to the WIFI dongle, which can be configured to connect to WiFi access to the Internet.

Enable: Wireless function to enable the switch

SSID: WiFi name, click the Scan button to search for nearby available WiFi routes.



When the list selects the WiFi that you want to connect to, double-click the WiFi name that you want to connect to

Rate: Signal intensity.

Security: Security protocol information used by WiFi.

Update: Refresh the list.


Password: Passcode for connecting the WiFi route.

IP Address: The IP address obtained after successfully connecting to the WiFi route.

Link Status: The connection status.

Default: Page configuration to restore the default. **Apply:** Changes to the application configuration.

5.5.1.5 port configuration



HTTP/RTSP/HTTPS: Set the port to access the device through the http/https/rtp protocol UPNP (Universal Plug and Play): UPNP full name universal Plug and Play (Universal Plug and Play), enables UPNP NAT conversion rules, realizes automatic port mapping, allows external computers to access Intranet devices, and makes the network work efficiently. The UPNP functionality requires the router support. Before setting the UPNP function, please set the router first, and set the parameters such as the Intranet IP address, subnet mask and gateway matching with the router in the basic network configuration.


Mapping Strategy: Select Manual, users can edit and set the external port (port on the router). if automatic, randomly map an external port (different from the internal port).

External IP: The external network outlet of the equipment is ip

Direct Camera Web Access: When enabled, you can directly access the WEB page of the IPC by hyperlink on the Web side of the NVR.

5.5.2 Cloud services

By enabling the cloud service function, adding the device to Risco sever.



Risco Cloud: Cloud service switch.

5.5.3 DDNS (Dynamic Domain Name Server)

This menu is used to configure the DDNS parameters. Using DDNS, through the domain name, can effectively solve the trouble caused by dynamic IP to access the device. To use DDNS, first need to open an account on the web page of the DDNS service provider.




DDNS: Check to enable DDNS.

Server: Select the preferred DDNS server (DYNDNS, NO_IP, CHANGEIP, DNSEXIT). **Domain:** Enter the domain name created on the webpage of the DDNS service provider. When connecting remotely to an NVR via a PC, this is the address that you need to type in the URL box. **User / Password:** Enter the user name and password obtained when creating an account on the DDNS service provider's webpage.

After entering all the parameters, click Test to test the DDNS settings. If the test result is Network inaccessible or DNS wrong, check whether the network is normal or whether the DDNS information is correct.

When the user applies for a dynamic domain name service, it can use the browser to remotely access NVR through the domain name in the form of http://domain name: mapped http port number. When using DDNS domain name to access NVR, it is necessary to confirm that the port and the current IP are normally connected on the public network, and the server address / host name / user name / password / setting is consistent with the NVR terminal setting.



Note: DNSEXIT The domain name provider has updated the docking protocol, and the new protocol no longer supports the verification of the user name and password. You need to log in to the original account through the official website and obtain the key (such as:


yUS5qMHQuPlJr4jHtoMuXDO883BqsO)

The previous version is authenticated by the password. If the external network IP changes, the DNSEXIT domain name will not be used. It must be updated to version 8.2.4.1 to go to the DNSEXIT official website to get key, and the domain name can be used normally after setting.


5.5.4 Email

This menu can configure email parameters. If you need to receive an alarm notification on your email when an alert is triggered, complete these settings.

5.5.4.1 Email Configuration



Email: Turn on the switch to enable it



Type: The mailbox type, you can choose the Outlook mailbox or the Other mailbox. If you need to click Activate, enter the authorization code according to the pop-up web page address for activation. It can be used successfully. If you use other mailbox, you need to enter the email address and password for activation.

Encryption: Enable if the e-mail server requires SSL or TLS validation. If not sure, set it to Automatic. SMTP Port: Enter the SMTP port for the e-mail server.

SMTP Server: Enter the SMTP server address for the e-mail message.

User Name: Enter the email address

Password: Enter your email password

Receiver 1~3: Enter the email address to which to receive an event notification from the NVR.

Health Mode: Health mode, enable Interval function if checked. if not checked, the Interval function will be unavailable, NVR alarm to the mailbox, for license plate and face recognition, you will receive the foreground map and background picture of the alarm picture.

Interval: The time interval between notification messages to configure NVR.

To ensure that all the settings are correct, click on Test Email. A test email is sent to the Inbox, and if the test email is received, the configured parameters are correct.


5.5.4.2 Email Schedule

Configure the time period and refer to 5.2.1.1 Record schedule.



5.5.5 IP filter

The IP filter function can set the black and white list, when the white list is enabled, only the IP in the list is allowed to access the device. when the blacklist is enabled, the IP in the list will not be allowed to access the device.



Enable: Turn the filter function on or off. When enabled, you can choose to enable Blacklist or whitelist.

Edit Filtering List: Select the list (blacklist or whitelist) to set.

Add Single IP Address: Add a single IP address.


Add IP Address Range: Add the IP address atmosphere.

Start Address: Enter the starting address. **End Address:** Enter the end address.

5.5.6 Platform Access

5.5.6.1 Onvif

Opening this function will allow the device to be connected as a server by a third-party platform through the ONVIF protocol.




Enable: Enabling switch, select the onvif service function of the device after saving. **Authentication:** Login authentication methods, equipment support authentication methods are Digest_sha256, Digest, Digest / WSSE, WSSE four

Protocol: Connection protocol supported by the equipment includes HTTP / HTTPS, HTTPS and HTTP.

Username: Set up the access user name. **Password:** Set up the access password.

5.5.6.2 RTMP

Using RTMP can be NVR channel audio and video stream pushed to YouTube website live in real time, use this function to register YouTube account, and create a studio, the studio site and live code, set to the equipment live server address bar, open and configuration stream type and live channel, save, to YouTube studio refresh page to watch real-time live.



Enable: Enable switch, open and save can enable RTMP live broadcast function.

Server Address: Fill in the live broadcast address and live broadcast code of the YouTube server.

(**Note:** "/" is used in the middle of YouTube live broadcast code)

Stream Type: Select the code stream type of the live broadcast channel to support the main stream and the sub stream.

Channel: Select the channel to live broadcast, only one channel.

Note: In order to ensure the effect of the live broadcast, it is recommended that the resolution setting of the code stream should not exceed 1920 * 1080


Only support live broadcast of video coding format H.264 and audio coding format G711A/U data stream.

Youtube live code can only be set for one device, and can not be reused.

5.5.6.3 Event Push Platform

To push the device side alarm information to the designated third party platform (using this function to ensure that the third party platform has completed the docking and debugging with the equipment) Event push is divided into HTTP push and UDP push: HTTP has POST method and GET method. UDP has three methods: unicast, multicast and broadcast.

HTTP



Enable: Start or turn off the event push function.

Name: Set up the name of the device used to send the alarm information to the third-party platform. **Push Method:** Support HTTP push mode and UDP push mode. HTTP is HTTP push mode and UDP is UDP push mode.

User Name: User name of the third-party platform

Password: Third-party platform password.

Server Address: Address of the third-party platform

Port: Third-party platform server port (port range 1-65535).

URL: the third-party platform server API interface.

Method: HTTP push type. POST method and GET method are supported: only HTTTP-POST method supports push, other only push message without push. push alarm type is consistent with the web preview warning bar.

Interval: warranty interval, according to the set time, the device will regularly send messages to the server, UDP no warranty mechanism.

UDP



Enable: Start or turn off the event push function.

Name: Set up the name of the device used to send the alarm information to the third-party platform. **Push Method:** Support HTTP push mode and UDP push. HTTP is HTTP, and UDP is UDP.

UDP Method: Support unicast Unicast, multicast Multicast, broadcast Broadcast three methods:


- **1. Unicast:** Enter the IP address and port of the client UDP server, and only this address can receive the push message.
- **2. Multicast:** Multiple client UDP servers can receive messages using the same UDP address and port, and other UDP addresses will not receive messages.
- 3. Broadcast: All UDP servers in the same network segment can receive messages.

UDP Address: UDP server address.

UDP Port: UDP Server Port (Port range 1-65535)

5.5.6.4 Cloud storage

The device will upload alarm pictures and video clips to the cloud for storage. The Dropbox / Google Drive can provide free storage services to meet the needs of cloud storage.



Before you enable cloud storage services, we recommend that you create an Dropbox account with a mailbox user name and password. After the creation, log in to www.dropbox.com, enter the email address and password, and click the login button after agreeing to the terms.

Enable: Check to enable the feature.

Type: Select the cloud storage type, with Dropbox and Google Drive.

Status: Active state of the cloud storage, not activated (Unactivated) and activated (Activated).

Capacity: Display the remaining capacity / total capacity.

Overwrite Storage: Set up the cloud storage overwrite mode.

Video Format: Set the uploaded video format, and support AVF, MP4, AVI format selection.

Folder Name: Set the folder name for storing the channel videos and images

Activate Cloud: Click to activate the cloud storage features. Later, you will see a message on the screen. You have the activation link sent to the email, check the email, and then click the link to activate the cloud storage.

5.5.6.5 FTP

Settings through this menu can meet the requirements of user alarm event FTP storage, and upload grab pictures and videos to the FTP server when the alarm is triggered.



FTP Enable: Click to enable the FTP functionality.

Server IP: Enter the FTP server IP address or domain name.

Port: Enter the FTP service port

User Name / Password: Enter the user name and password of the FTP server.

Picture Quality: Set the quality of the image uploaded to the FTP.

Video Stream Type: Set the type of video stream uploaded to FTP, with master and substream optional.

Max Package Interval: Set the maximum video time interval, that is, what is the maximum video time of an event, after which another video file will be created to continue recording.

Directory Name: Enter the directory to save the uploaded files. When NVR starts to upload the files to the FTP server, it will automatically create a new directory under the server to store the files.

Upload Alarm Video: Set the warning type for uploading the video to FTP. After clicking the option, you will enter the warning menu in the corresponding alarm type.


Test FTP: Click to test the FTP settings.

5.6 System Settings

Change system information, such as date, time and region, change password and permissions, etc.

5.6.1 System

5.6.1.1 General



Device Name: Set the device name

Device ID: Set up the device ID. The device ID is used to identify the NVR, and is only composed of numbers. For example, install 2 NVR in the same location, with one NVR device ID 000000 and another NVR device ID 111111. When operating an NVR with the remote control, both NVRs may receive signals from the controller and act simultaneously. If you only want to control the NVR with ID 111111, you can enter the device ID 111111 in the login page with the remote control for further operation.

Language: Set up the system language of the device

Video Format: Set the video system to PAL or NTSC.


Auto Lock: Set the timeout time to exit the main menu and lock it out when the system is not operating

Web Session Timeout (min): Set the timeout time when the web is idle

Including Live View: The idle login time on the web side is applicable for preview.

Show the Startup Wizard after system startup: If you need to display the boot wizard at each boot time, check this option.

5.6.1.2 Date and time




Hide Date, Time, Time Zone and NTP when the Risco Cloud switch is open.

Date Format: Set the system date display format.

Time Format: Set the system time display format.

off Risco Cloud switch:



Date: Click the calendar **t**o change the date.

Time: Click on the time box to change the time.


Date Format: Set the system date display format.

Time Format: Set the system time display format.

Time Zone: Set up the time zone of the device.

NTP (Network time Service)

Enabling the NTP function will allow NVR to automatically synchronize the time with the time server, and NVR will regularly request updates from the server and correct the time of the NVR system to ensure the accuracy of the device time.




Enable NTP and select a server address or manually enter a server address that supports NTP timing, click **Update Now** to manually synchronize the date and time.

Click **Apply** to save the settings. After the NTP function is enabled, the device should be ensured in the network state, and the device will automatically correct the system time at each startup and around 00:07:50 every day.

5.6.1.3 Daylight Saving Time

If the Risco Cloud switch is on, settings cannot be modified.

Off the Risco Cloud switch, If the DST daylight time is implemented in the user area, relevant parameters can be set in this interface and DST can be enabled.




Enable DST: Daylight saving time switch

Time Offset: Set the daylight saving time offset time duration.

DST Mode: Set the start and end mode of daylight saving time.


Week: Choose the start and end month, specific week and time. For example, at 2 am on the first Sunday of a certain month.

Date: Select the start date (click the calendar icon), date and time to start and end daylight. Start Time / End Time: Set the start time and the end time of daylight saving time.



5.6.1.4 Output configuration

Set the system display output parameters.



Select the LIVE-OUT mode in the Video Output drop-down menu.

Cycle Mode: Set the number of video channels displayed by NVR in wheel patrol mode.

Cycle Dwell Time: Set the wheel patrol time in seconds.

Output Resolution: Select the display resolution suitable for the display.

Automatic recognition: Automatic identify the resolution of the display, after the startup when the detection of the system when the resolution of the highest resolution supported by the display, and prompt to switch to the appropriate resolution.

Scale & Offset: NVR supports adjusting the size and position of the display to match the display.

Click the Settings button to adjust.



Scale: Scale up the displayed screen size.

X Offset: Move the screen to the left or right.

Y Offset: Move the screen up or down.

You can resize and position by clicking once or pressing the left mouse button on the arrow, or you can scroll the mouse wheel to adjust. Right-click to exit, and click Apply to save the changes.


Cursor Hide Delay: Set the time to hide the mouse cursor when the NVR is idle.

Cursor Acceleration: Adjust the speed of the cursor movement.

Transparency: Click and hold the left or right slider to change the transparency of the menu bar and the main menu on the screen.

• HDMI 2

Set auxiliary screen display output parameters (only some NVR models support)



Switch: Enable or close the auxiliary screen display switch.

Auto Cycle: View Settings, optional static, dynamic two, select dynamic screen will be on the auxiliary screen round preview.

Cycle Mode: Set the number of video channels to be displayed by the device in the HDMI 2-round patrol mode.


Cycle Dwell Time: Set the patrol time on the auxiliary screen wheel in seconds.

Spot Display Channel: Select the channel of the auxiliary screen wheel patrol in dynamic mode.

Output Resolution: Select the display resolution suitable for the auxiliary screen display.

Decode Performance: Set the decoding performance of the auxiliary screen output.

5.6.2 Multi-user management




The system supports the following user types.

- ADMIN- -System Administrator: The administrator has the highest permission to configure
 the system, and can change the administrator's password and user password, and enable /
 disable password protection.
- USER- -Ordinary user: users can only get access to preview, search, playback and other functions. You can set up multiple ordinary user accounts with different access rights.


Default Login User: Default user, that is, the default user of NVR restart to log in.

5.6.2.1 Change the password and the single user login number


Need to change the password of the administrator or ordinary user, click the icon, the password should be set to 8-16 bit characters, the password should not be set to be the same as the user name, including at least two kinds of numbers, capital letters, lower case letters or special characters, Maximum access users (1-20 supported or unlimited), click Save to save settings.



5.6.2.2 Add new users



3. Select one of the users currently inactive, and click user edit icon.




- 4. Open "Enable Switch" to enable the user.
- 5. Click **User Name** to edit the user name.
- 6. Click on the Password area to enter the desired password.
- 7. Click on the ${\color{red}\textbf{Confirm}}$ area to re-enter the password.
- 8. Click Max. Login Number to set the maximum number of access users allowed by the device.

5.6.2.3 Set the user permission

The Administrator account is the only account that has all control of the system, and this page can enable or disable certain menus and functions for each regular user.

1. Click the Edit icon under the Permissions tab



2. Set the user's permission and check the box corresponding to the function. Click All to select all of the boxes. Click Clear to clear all of the boxes.

User password permission setting, the administrator can select the permission of ordinary users as required.

Have the following privileges to select.


- **Log search:** you can view the device's log.
- **Config Parameter:** you can set the parameters of all the pages.
- Auto Reboot: automatic maintenance and restart of operable equipment.
- > Manual Record: Manually start video recording and can manually stop video recording.
- ➤ Hard Disk: Operate and set the hard disk.
- **Remote login:** Users have remote access to NVR.
- **Auto cycle control:** Rotation to view the real-time preview of all channels.
- > Manual capture: Manual start capturing.
- ➤ Audio: Control the channel audio control and intercom.
- **Face database management:** whether you can operate the face database.
- ➤ License plate management: whether the license plate database can operate the license plate database.
- Change password: whether the sub user login can modify the subuser password.
- Backup: After opening the Backup channel to enable the switch and select the backup channel, the average user has permission to back up the video of the selected channel.
- **Preview:** Open the Preview enable switch and select a channel for preview viewing, and the average user has the permission to monitor the real-time preview of the selected channel.
- ➤ Video playback: After opening the "video playback" enabled switch and select the channel to view, the average user has the permission to replay the selected channel video.

- > PTZ: open the "PTZ" enabling switch and select the operational channel, the average user has the PTZ operation permission.
- **3.** Click **Save** button to save the modifications.

5.6.3 Maintenance

5.6.3.1 Log

The system log records the relevant system event information, such as various types of alarms and system operation records.



Log Search and Backup:

- 1. Click the area next to Start Date and Start Time to select the start date and time of the search from the screen calendar.
- 2. Click the area next to End Date and End Time to select the end date and time of the search from the screen calendar.
- **3.** Select the type of event you want to search from the drop-down list next to the Log Type, or select All to view the entire system log for the selected time period.

System: Record the log information of system setting, restart, automatic restart, upgrade, time setting and NTP timing.

Configuration: Record preview control, privacy area setting, recording mode setting, recording schedule settings, main code flow settings, network settings, subcode Settings, mail settings, color setting, motion detection settings, hard drive settings, multiple users, NTP settings, image control, the third stream settings, RTSP settings, IP filter Settings, system recovery Settings from the factory Settings, audio Settings, video Tampering alarm Settings, export Settings and import Settings operation logs.

Alarm: Record the alarm information.

Account: Record the login and login records of local or external visitors.

Record: Record the operation log of search, playback and backup.

Storage: Record log information such format hard disk, hard disk full and hard disk errors.


AI: Record the alarm information of intelligent events.

4. Click Search to Search.

- 5. Browse through the system log from the selected time period:
 - o Events can be played immediately by clicking Playback.
- **6.** Click **Backup** to create a backup of the system log. Ensure that the external storage device is connected to the USB port of the NVR.
- 7. The Backup drive menu appears. Navigate to the folder where you want to save the backup file, and then click OK to Start.

5.6.3.2 Restore factory settings

This page supports various ways to restore the NVR parameters to the factory settings. Once the data is cleared, it cannot be restored. Please choose carefully.



Restore to Inactive: Reset the administrator password, delete all sub-users, the device needs to be reactivated, and other page parameter settings remain unchanged.


Restore Defaults: Except for the basic network parameters and administrator password, all the parameters of other pages are restored to factory Settings.

Factory Defaults: All the parameters are restored to the factory settings.

In addition, the device supports press the RESET button on the rear panel for 10 seconds to perform the corresponding recovery mode. Check **Format HDD** to format the hard disk at the same time. Once the data will not be recovered. Please choose carefully.

5.6.3.3 Upgrade


5.6.3.3.1 Udisk Upgrade



- **1.** To send the firmware file (.bin file) copy to the USB drive and then insert the U disk into the USB port of the NVR.
- 2. Click Select File to select the firmware file in the USB Flash drive, and then click OK.
- **3.** Click the upgrade button to start the system upgrade. The system upgrade will last about 5-10 minutes. Do not power off the NVR or remove the U disk from the NVR during the firmware upgrade.

5.6.3.3.2 Online upgrade

The device supports the online upgrade function. If this function is used, you should set up the upgrade server in advance, and create a file storage directory on the server, and upload the upgrade firmware to complete.



Username: Set the server user name, if the server does not set the user, here can be empty **Password:** Set the server password, if the server does not set the password, here can be empty. **Server Address:** Set the server address, and the upgrade address should be specified to the storage directory of the upgrade file.

Automatic Detection: Automatic detection. After enabling, the device will check and upgrade the firmware from the server regularly during startup and during operation. If there is an updated firmware, a popup will be prompted.

Detect Now: Click the button to manually check the server for upgradable firmware.

Upgrade: When the server detects renewable firmware, this button will be highlighted and click OK to allow the device to upgrade.

5.6.3.4 Parameter management

Users can export the currently configured parameter file to the U disk, or import the exported parameter profile from the U disk into the same model device.




Save Settings: Save the current device system configuration parameters to the specified USB storage directory.

Load Settings: Import the configuration parameters in the USB storage directory into the current device, and the device will automatically restart after the import completes.

5.6.3.5 Automatic maintenance


This menu allows the system to restart regularly, and it is recommended to keep this function enabled.



Auto Maintenance: Enable or close the automatic maintenance function.
Maintenance Interval: Set the automatic maintenance cycle of the equipment.
Maintenance Time: Set the equipment automatic maintenance period.(Note: Device will restart at random time during this period)

5.6.3.6 Developer Mode

When the system has an exception, developers can collect the serial port log information when the system runs through this page to locate the problem.



Recorder Debug: Set whether the video recorder enables the debug mode and the output position of the debug log.

Disabled: Do not save the serial port log.

Output To Terminal: Export the serial port log to the terminal.

Output To Hard Disk: Save the serial port log to the hard disk.

Download Debug Logs: Export the serial port log to the U disk.

Clear Debug Logs: Delete the collected serial port log in the hard disk.

Camera Debug: Set whether to record the serial port log of the camera to the video recorder. After selecting and saving the channel, the camera debugging log of the corresponding channel will be transmitted to the video recorder side for preservation.

Camera Channel: Select the camera channel from which to export the debug log.

Log Duration: Select the period in which to export the debug log.

Download Debug Logs: Export the camera debugging log to U disk and support saving according to the channel and recording time.


Clear Debug Logs: Delete the stored camera debugging log in the hard disk.

Device Status Reporting: Enable this function to upload the storage status, channel status and device information of the device to the P2P server.

SSH Service: When enabled, the device can be accessed using the SSH mode.

5.6.4 IP Camera Maintain

5.6.4.1 IP Camera Upgrade




- 1. Select the IP camera to upgrade.
- 2. Click Select File, select the upgrade file from the USB storage device, and then click OK.
- **3.** Click the camera **Upgrade** button to start the upgrade. Do not power off or unplug the U disk for the NVR and IP cameras during the upgrade.

Automatic Detection: Automatic detection. After enabling, the device runs for 24 hours, and it will detect the latest upgrade file in the server. If so, it will indicate whether to upgrade.

Detect Now: Manually detect the latest upgrade file.


Upgrade: If the latest upgrade file is detected, please click to upgrade.

5.6.4.2 Load Default




- 1. Select the IP camera where you want to restore the factory settings.
- **2.** Click **Load Default** to restore the factory settings, you need to enter the administrator password for authentication.

5.6.4.3 Reboot Camera




Click the IP camera and click Reboot Camera to restart IP camera.

5.6.4.4 Parameter Management



After checking the IP camera, click **Save Settings** to save the IP camera parameters to the U disk. After selecting the IP camera, select the saved parameter file, click **Load Settings** can import the IP camera parameters. Note: The parameter file must be imported into IP camera of the same model.

5.6.4.5 Format Camera's Storage



The system can detect the IP camera already connected to the SD card. Click **Format** button to format the SD card of the IP camera.


5.6.5 Information

5.6.5.1 System information

View the device ID, device model, IP address, MAC address, firmware version, etc.




5.6.5.2 Channel information




View channel information for each connected camera, such as alias, primary, child, and thirdstream recording parameters.

5.6.5.3 Record information



View the recording information for each connected IP camera, such as the bit rate, code stream type, recording resolution, and frame rate (FPS).

5.6.5.4 Network state



Port	
Http	80,80,Inactive,Disable
RTSP	554,554,Inactive,Disable
Https	443,443,Inactive,Disable
Total Bandwidth:	128Mbps
Used Bandwidth:	31.5Mbps


View the system network information.

Total Bandwidth: Reflects the total input bandwidth of the NVR used for the IP camera.

Used Bandwidth: Reflects the bandwidth used by the IP camera.

5.6.5.5 Privacy Statement

Users can view the specific content of the device's privacy statement on this page.




Chapter 6 Al Scenario

6.1 Crossing counting scenario

This is an AI application based on cross-counting functions that helps control the attendance of customers / visitors / vehicles in public places such as restaurants, parks, zoos, theaters, museums, parking lots.

6.1.1 Channel

By single camera counting and viewing real-time results. Mainly used for a single entrance of small places.



1. Channel drawing and real-time crossing statistical data, you can select the drawing channel in the Channels in the Settings.



Available: Number of remaining presence allowed **Inside:** The current existing quantity in the control area


Enter: Number of entries recorded **Exit:** Number of exits recorded

- 2. Select the number of drawing windows , with four windows , six windows and nine windows. display / hide the statistics under the channel. click clear the current selected channel statistics and clear all channel statistics.
- 3. Real-time count data information , click to display the total statistics on the full screen.

4. Data of entry and exit information of each channel and each time period.

6.1.2 Group No

Statistics and view real-time results by group. It is mainly used in large places with multi-channel entrances and is monitored by multi-channel cameras.



- **1.** Group can select the group information displayed, Live displays the channel preview screen and statistics information, and Map displays the map information.
- 2. Channel drawing and real-time line crossing statistical data, you can select each group drawing channel in the Group in the Settings.



Enter: Number of entries recorded **Exit:** Number of exits recorded

- 3. Select the number of drawing windows with four windows, six windows and nine windows. click to display / hide the statistics under the channel. click to clear the current selected channel statistics and click to clear all channel statistics.
- **4.** Real-time count data information, click to display the total statistics on the full screen.

Available: Number of remaining presence allowed **Inside:** The current existing quantity in the control area

5. Entry and exit data information of each group during each time period.


6. Map information configuration click to add a map picture, click to set the position of the IPC diagram on the map, click to display the map information and the statistical information of the current group in full screen.

6.1.3 Search




You can search for channels and groups separately. Select the channel or group that you want to search for, set the search duration by day, week, month, or year, and select the target type that you want to search for. Click the search icon and the results appear on the right side of the window.

6.1.4 Setting-up




1. Check Advertising mode to open advertising mode. set the picture playback residence time in seconds, the default is 3 seconds. Click the ImageFile (s) button to import the AD images to be displayed from the USB directory, supporting up to 16 images in jpg, png and bmp format, with a resolution not more than 2560x1600.



2. Click Add New Picture, and click Delete the added pictures one by one.

If you want to display an image with the original aspect ratio, select Keep Aspect Ratio. if you want the image to stretch and display in full screen, uncheck the box. Enter the channel mode or group mode, click the full screen button in the upper right corner of the page to display the AD picture and real-time count data.

3. The Set enable box selects which channels to display on the channel page. If the camera in the channel supports AI, the setup and alarm icons will be blue. Instead, if the camera does not support AI, the icon will be gray. Set up the Capacity for each channel, which is the maximum limit for attendance. Click the configuration detection condition of Setup, and click the Alarm configuration o enter the alarm action when the number is 0.



Buzzer: Set the buzzer duration in seconds when the available number is 0.

Alarm Out: If NVR supports connection to an external alarm device, set the external alarm device when the alarm triggers.


- 4. Click \the Add IP camera icon to add channels to the group. Up to eight groups can be set, but only one channel can be added to one group. If channels are enabled in channel view mode, they are not allowed to be added to any group. Select the Enable box to activate the group. You can set the number of Capacity per group, Start Time, End Time, detection type (Person, Vehicle and Motion).
- 5. Click the configuration of Alarm to enter the alarm action when the number is 0.

6.2 Face Attendance


The full-screen display can record the face attendance in real time and check the attendance results in real time




- 1. Face attendance interface theme.
- 2. Click button to enter the playback face attendance search interface, and select the face pictures in the face group by default



3. Click to enter the setting interface.



Channels: You can select the attendance channel




Groups: Select the faces of those face groups for attendance, and click on the right to pop up to the AI face bank setting interface.

GUI Theme: Interface theme


Start Time of Work: Set the working hours **End Time of Work:** Set the closing time

Email Configuration: Face attendance result to send the mailbox configuration, click to send the face attendance result email configuration




Enable: Open the email to send the face attendance results (the attendance result is a table file)

Email: Set the time for sending the face attendance result email. Click the pop-up system mail setting interface on the right side of the sending time to configure the system email



Mode: The mode of sending face attendance results is: Day, Week, and Month


Day: Send once a day, send yesterday's face attendance results.



Week: send once a week, can choose the week to send sent face attendance results for the time to send mail forward a week, such as,

Send an email on Monday, and the attendance record is Monday to Sunday

Send an email on Tuesday, and the attendance record is from last Tuesday to this Monday.



Month: send once a month, you can choose the date of each month to send the sent face attendance results for the email time forward one month, such as:

If an email is sent on the 10th of each month, the attendance record is from the 10th of last month to the 9th of this month

That is, if the email is sent on May 10th, the attendance record sent is the attendance record from April 10th to May 9th

Working Days: Select a working day, and select every day is a working day

Apply: Click on Apply to save the settings

Default: Send the attendance email setting to restore the default

Show the current date and time

Current total number of people attendance situation

Total number of attendance required

Number of attendance

No attendance

Attendance status of each face group

Channel diagram, the channel can be selected in the Channels inside

- 4. Select the number of exit windows with exit windows and exit windows with exit windows
- **5.** Face real-time attendance push, display attendance face picture, name, from the group name, work attendance time and off-work attendance time
- **6.** The interface also shows the maximum number of face attendance push, with 1, 6


and 1

6.3 Non-motor vehicle statistics


Face, human form, motor vehicle, non-motor vehicle detection scene interface full screen display, the detection results can be viewed in real time.



- 1. The interface theme of computer-nonhuman statistics
- 2. Click to enter the playback humanoid model search interface.



3. Click to enter the setting interface.



GUI Theme: Interface theme

Statistics: Statistical time, you can choose 1 day, 2 days, 3 days, 4 days, 5 days, 6 days, 7 days, week, month, year.

Channels: Channel selection, you can select the statistical channel.


- 4. Show the current date and time.
- Channel drawing, and the drawing channel can be selected in the Channels inside.
- **6.** Select the number of drawing Windows, with Windows drawing Windows, with Windows drawing
- 7. Real-time push display switch, click the icon to display / hide the corresponding detection results for real-time push
- **8.** Real-time push of face detection, showing the detected face picture, the name, and the incoming group name.
- **9.** Real-time push of humanoid detection, display the detected humanoid images, detection channel and detection time


- **10.** Real-time push of motor vehicle type detection, and display the detected motor vehicle pictures, detection channels and detection time
- **11.** Real-time push of non-motor vehicle type detection, showing the detected non-motor vehicle pictures, detection channels and detection time
- **12.** Statistics of the number of human faces, human shapes, vehicle models and non-motor vehicles captured.

Chapter 7 Playback Search and Backup


7.1 Use of the search function

Click or icon to search in the system menu to enter the search playback interface.






- **1. Search options:** The system provides a variety of search and playback methods: general, event, slice playback, intelligent, tag playback, external files, pictures, slice playback, and AI.
- 2. Search Date: Select the playback date.
- **3.** Channel selection: Select the channel to search for and play.
- 4. Video playback control: controls the playback of the video.



7.1.1 Playback interface search and playback video

recording



- 1. Select the search date in the calendar.
- **2.** Select the search channel.
- 3. Search results will be displayed on the 00:00-24:00 timeline.
- **4.** Click the \triangleright icon to start the play.
- **5.** Control the playback by using the icon on the video playback control.
- 6. Select or swipe the mouse wheel to view smaller or larger time periods.
- 7. If you want to quickly save a video during playback, you can use the video clip backup function.
- 8. Click Add a custom tag to make a mark at the current time of the current channel. After the addition is completed, you can jump to the previous "mark" in the label playback interface.


7.1.1.1 Smart pattern



After selecting Smart search, click the pedestrian type and vehicle below buttons, and the video progress bar will mark the alarm video of the trigger person and car type in blue. The alarm

video of human and car type includes the video of human model events detected by Pedestrian & Vehicle, Intrusion, Enter Region, Exit Region, Line Crossing and SMD.

Click the Policy Playback button to adjust the playback strategy.




Do not play normal video: Check the Normal event type video of the day will not be played, but only play the alarm event video of the searched human model at the double speed set by Smart / Events Video.

Normal Video: If Do not play normal video is not checked, you can set the double speed for video playback to the Normal event type. After **Do not play normal video** is checked, the popup will be displayed.

Smart / Events Video: Set the double speed of the alarm event video played to a human model. **Note:** Only single channel search playback main stream video is supported in Smart mode.

7.1.1.2 Motion Search



The device detects a Motion-Search type, which is displayed in yellow in the time bar below the progress bar. Click to enter the Motion-Search loconing interface.



The red box is the selected area. If there is a picture change in the area, it will be searched out and mark the time bar with yellow.


7.1.1.3 Video clip backup



- 1. Insert the U disk into the NVR.
- 2. Select the backed-up channel to start the video playback.
- 3. Click the clip icon.
- 4. Move the mouse cursor to the timeline in which to start the video clip.
- **5.** Hold down the left mouse button and drag the cursor to the timeline where you want to end the video clip.
- 6. When the icon changes to the icon to save the clip of the video clip.
- 7. Select a file type for the backup file, and click the Save icon to save the video clip. Please make sure that the USB storage directory has enough space to save the video clips.




- 8. The Backup menu page appears to select the directory to be saved
- **9.** Click OK to start a backup. The progress bar at the bottom of the window shows the progress of the backup.



7.1.2 Sub-Periods

Sece playback can play event video of multiple periods in a single channel. The searched video period will be split according to the selected split screen mode. For example, if the searched event video time is 60 minutes long and the split screen is x 4, each split screen will play for 15 minutes.



Strip search for playback video:

- 1. Select the date and time of the search.
- 2. Select the number of split-screen plays for the video channel.
- **3.** Select the type of video that you need to search for, or select All.
- **4.** Select stream type and search channel (only one channel)


- 5. Click the play icon to start the play, and control the play by the icon on the video playback control.
- 6. Click the left mouse button on a specific split screen, and the time period of the video split screen will be displayed on the timeline. The color bar at the top of the timeline indicates the time span of the video split screen that you clicked on. The color bar at the bottom of the timeline indicates the time span of the entire video already searched.



7. Select or swipe the mouse wheel to view smaller or larger time periods.

7.1.3 Slice Playback

The page refines the video of the search to every minute display.



Select Code stream, Channel, Month, Days, and Hours, then, to display 60 current hours on the right, each for 1 minute. Click to do a simple playback in the lower corner. Click to access the normal playback.

View mode: If you choose the channel (Channel), the selection before the search can only select the channel first, and if the time (Time), the selection before the search can only be selected first.

7.1.4 External files

You can play the video file in the external U disk, select the left file list, and click the play button to play.



7.1.5 Event search, playback, and backup

Through the event search page, you can view the list of each event video, showing detailed the channel, start and end time, memory size, and event type of each event.



Event search, playback, and backup:

- 1. Select the date and time that you want to search for.
- 2. Select the type of video that you need to search for, or select All.
- 3. Select how long it takes the event to start playing. how long it ends.

- 4. Select the channel that you want to search for, or select all of the channels.
- **5.** Click on the search icon to search.
- **6.** Events that meet the search criteria are displayed as a thumbnail view. Double-click one of the events to play the event video immediately.
- 7. Clicking the icon in the lower between event pages or enter the page to browse.
- **8.** Switch the view of the list form by clicking the icon in the lower right corner of the screen:
- Thumbnail view: You can view the snapshots of the event.

 List View: Events will appear in the list.

Details View: You can view the details of the event.

In Detailed View mode, video events to prevent them from being covered by the hard disk. Click the icon to lock or click the icon to unlock the event.

- **9.** When the left mouse button is clicked on the event, the event information is displayed in the lower left corner of the screen.
- 10. In descending order: arrange the file list in descending order.
- **11. Select:** Select the check box before Event Number to select events, the check box before Select Current Page to select all events in the current page or the check box before Select All Pages to select all events.
- **12.** The selected number of files and total size information will be displayed in the bottom right corner of the screen.
- 13. After selecting File, click the icon to save the video to the U disk, or click the icon the event playback control window to play the video.

7.1.6 Picture search

This page can search for all images saved to the hard disk.



- 1. Search, play, and back up the images:
- 2. Select the date and time of the search.
- 3. Select the picture capture type you want to search, or Search Type to select all.
- **4.** Select the channel to search for
- **5.** Click on the icon to start the search.
- 6. Pictures that meet the search criteria are displayed in a thumbnail view. Click the button the upper right corner of the thumbnail to view the image, and click the button in the middle of the thumbnail to play the front and back video of the time point of the image.
- 7. Clicking the icon in the lower between event pages or enter the page to browse.
- 8. Switch the view of the list by clicking the icon in the lower right corner of the screen below.
- Thumbnail view: View a picture of the event.


 List View: The picture appears in the list.

 Details View: View the details of the picture.
- **9.** When you click the left mouse button on one of the pictures, the system displays the picture information in the lower left corner of the screen.
- 10. Select: Select the check box before Image Number to select images, the check box before Select Current Page to select all images in the current page or the check box before Select All Pages to select all images.
- **11.** The selected number of files and total size information will be displayed in the bottom right corner of the screen.

12. After selecting File, click the icon to save the picture to the U disk, or click the icon enter the event picture playback interface.

7.1.7 Tag playback

This page can view all added tags and edit, replay, or delete. Select the time and channel to click to complete the search. Click to jump to the position marked by the label for playback.




Keyword: Enter the keyword in the label name fo accurate search.

7.1.8 AI

7.1.9.1 Face

After selecting the date, time, channel and face event, click search to search the all face information of the event during that time.



1. Click to customize the added search face. Or select Event Select All Face Event for contrast search.


Face recognition alarm: Face recognition after enabling Alarm linkage.

Frequent persons alarm: trigger the face grasp map after personnel frequency analysis and alarm. **Others:** Face recognition after not enabling Alarm linkage and face capture after triggering face detection.

Note:

A. Face recognition refers to face alarm detected after importing face information and enabling at least one face group. face detection means no face information or imported face letter information but all face group is not enabled.

B. Alarm linkage refers to the Alarm enable switch on the face database page, as shown in the below picture.



- 2. Click Channels to select the channel for the search
- **3.** Click Attributes to set the face attribute conditions for search, select Gender, Age, Mask, glasses and expression.
- 4. Select Alarm Groups Select the face group with the face contrast
- 5. Select the picture in the search area, click to delete the picture, and click to pop up to the face database setting interface.
- 6. In the search results, right-select import this image into the face library grouping.
- 7. Right-select Detail Information in the search results to view the details of the face.
- 8. Click Custom Playback to enter the time when the face is detected for playback.
- 9. Click to view the different viewing methods.

7.1.9.1.1 Face track map

1. Click on the lower right corner to enter the electronic track chart menu.




2. Click Load Map to pop up U disk, select map Add. Check Edit to drag the IPC icon to the place you want to place and unexit edit mode. Then click, select the face from the local face library or U disk, click search (only support the search for one face), you can search out the IPC that has detected the face, and there will be a color mark on the map.



3. If you click the left button on an IPC icon and play it back, there will be a simple playback in the lower right corner. If more than one IPC detects the face, the click player will automatically determine the person's movement and introduce an arrow.

7.1.9.2 License plate

If the camera turns on the license plate detection, triggers the alarm and records the video, view the video details or export it in this interface.



Time: Set the time period. The date can be set by clicking.

License Plate: Screen and query according to the license plate information.

Fault-tolerant: Fault tolerant character, which allows the number of characters inconsistent with the set license plate number. The lower the setting, the higher the matching degree of the search results.

Note: If you want to search for the target license plate by entering only a few characters, the fault tolerance rate can be set to the maximum. At this time, many unrelated license plates will be found, but the search results are sorted by similarity, similar and high license plates are in front, and you can find the desired target license plate.

Snapped Information: Details of alarm events have the following five items:

Channel: Video shooting channel in the event.

Start Time: Start time of the event trigger.

End Time: End time of the event trigger.

Snaped License Plate: The camera captures the license plate number by taking the license plate photo.

Capture License Plate: Compare the license plate number obtained from the database.

Sort By: Event videos are sorted by time.

Channels: License plate detection events triggered by each channel can be searched.

Search: Query according to the selected settings.

Alarm Group: Select different groups in the database to compare and search to display the results.

This function is to click the triangle icon in the lower right corner of the event video to select the delay of playing the video. There are the following: 5s, 10s, 20s, 30s, 1min, 2min, 5min, 10min, Custom Playback. If 30s is selected, the video will be extended by 30 seconds each.

Video can be backed up to U disk, and the video format supports AVF, AVI and MP4.


Select All Selected: 4 All the videos selected and the number of videos selected.

Click to turn the page.

Click to View select different views.

Select an event right-click gives two options:

Detail information: View the event details.




Custom Playback: Playback setting, click, you can set how long the event plays in advance and how long the delay will end. The maximum time period was 10Min.

Double-click the event or drag to the lower left corner to play the event video.

7.1.9.3 Pedestrians and vehicles


1. After selecting the date, time, passage, pedestrian and vehicle type, click search, you can search for all pedestrian and vehicle information in this time period.



2. Left click on the left will have basic information, right click to customize the playback and view the details. Click on the lower left corner to play for simple playback, double-click to zoom in, and enter the normal playback mode.

7.1.9.4 Line Crossing


1. After selecting the date, time, channel, and alarm type, and person and car type, click search for the alarm information triggered by the grouped person and car during this time period.



2. Left click on the left will have basic information, right click to customize the playback and view the details. Click on the lower left corner to play for simple playback, double-click to zoom in, and enter the normal playback mode.

7.1.9.5 Intrusion / Enter Region / Exit Region


After selecting the date, time, channel, and detection target type, click **Search** to search out the alarm events captured in the selected time period.



7.1.9.6 Repeat Visitors

7.1.9.6.1 Real-time Repeat Visitor

Search Mode Select Real-time Search to retrieve the statistical results of the personnel frequency analysis.




- 1. Select the date and time that you need to search for.
- 2. Select the face library group to compare and search group by default.
- 3. Select the minimum and maximum number of people to search (over 20 times please enter 21).

- **4.** Click the Search button, display the search results on the right side, and display the number of times of the person at the bottom of the face grab map.
- 5. Click the search results, there will be detailed playback and information on the left, right click to import the face library or edit the face library image information and view the detailed information.
- **6.** Click Sort By to sort, in order of time or quantity.
- 7. Check the search results or Select All. Check all the search results, click the icon to customize the play, or click the picture and video backup to the USB storage device.

7.1.9.6.2 Database mining


Search Mode Select Database Mining can be retrieved and counted for the number of times of the same face according to the similarity and face attributes.



- 1. Select the date and time that you need to search for.
- 2. Select the face library group to be compared, and search group.
- Select the channel that you need to search for.
- 4. Select the corresponding face attributes in the face attribute interface.
- **5.** Enter the number of seconds of the minimum interval.
- **6.** Left click the search result, click the search result, there will be a detailed playback and information on the left, right click to import the face library or edit the face library picture information and view the detailed information.
- 7. Enter the minimum number of face appearances at Minimum Times for screening.
- 8. Click Sort By to sort, in order of time or quantity.
- 9. Check the search results or Select All, select the search results, click the icon play or click the picture and video backup to the USB storage device.

7.1.9.7 Face attendance

The attendance system can check if someone appears within the specified time. And automatically determine whether they are late or leave early.




- 1. Channels: Choose the channel for face attendance
- 2. Select Mode: Select the face picture of attendance, By Group and By Person


By Group: Select the face picture through the face group, that is, add all the face pictures of the group.

By Person: Select the face map, click the right button to pop up the face map interface of the face library.

- **3.** Date: Select the search date, the default is the system time day, there are five selection modes: Day, Week, Month, User-defined, Today.
- 4. Working Days: Select working days
- 5. Start Time of Work: Set the working hours
- 6. End Time of Work: Set the closing time
- 7. Click on the Search. You can search out the results.



8. Click on a result, and all the detection records will be displayed below. Click to the detail icon to enter the details interface.



There are details on attendance, including the first appearance and the last appearance. Click make a simple playback in the lower left corner.

- 9. Click Export to save the searched attendance information generation file to the U disk.
- 10. Click Email to send the searched attendance information generation file to the mailbox.

Chapter 8 Remote Access through the Web Client

Access the device remotely at any time through a PC using a Web client. Make sure the device network is working before accessing the Web client.

8.1 Basic environment requirements of the system

The minimum requirements for the hardware and operating system required to run the Web client are shown below.


project	least value	Recommended value		
CPU	Intel® Core™ i5 CPU	Intel® Core™ i5 CPU or higher		
Run memory	4G or more	8G or more		
hard disc drive	And 500G or more	And 500G or more		
Display memory	2G or more	4G or more		
Displays the resolution	1280*1024	1920*1080		
OS	Windows 7 Or above Mac OS X® 10.9 or above			
DirectX	DirectX 11			
Direct3D	Acceleration Function			
Ethernet adapter	The 10 / 100 / 1000M Ethernet adapter			
IE browser	Microsoft IE browser (Vers	Microsoft IE browser (Version: 11,10)		
Firefox browser	V52 and above			
Google browser	V57 and above			
apple Safari	Version 12.1 and above			
Edge browser	V79 and above			


8.2 Download and installation of the Web plug-in

To access the Web client, follow these steps:


1. Open the browser, enter the IP or DDNS + port number of the device in the URL box, and enter the correct user name and password in the user information verification page to login to the web client. (Five consecutive password errors will be locked for 180s)

The RISCO sever can set the web login time, When the login times out, IPC can't login to the web client.





2. When you first visit the IE browser, the system will require a plug-in. Click on Download and install the player to download the plug-in and install it to the computer.



3. After installing the plug-in, refresh the page, click the permission in the pop-up window at the bottom of the page, and then use the diagram normally.

Note: When using Apple Safari / Google browser / Firefox browser / Microsoft Edge browser, you do not need to download the plug-in, and you can directly login and access to the device.

8.3 Web Client Management

8.3.1 Preview interface

After the Web side verifies the user information through the device, enter the real-time preview page of the device. This page can open or close the real-time preview, manually record video to the local computer, snapshot of the screen, cloud head control, color adjustment, etc.



1. List of channels

Click the list of channels.

Turn the live video stream on / off , and the icon appears blue when the live video stream is on.

Click to start manually recording the streaming video. Click again to stop the recording. Manual video recording is saved to the computer. On video recording, the icons are colored in blue.

Manual snapshot icon. Click to save the current live-displayed snapshot to the computer.

Bitrate icon. The camera is set to use mainstream, substream or mobile stream video settings, which is only for IP channels.

2. Code flow switch

The Web automatically cuts into the main stream mode when watching single split screen, and into sub stream mode when watching multi-split screen. Users can select the appropriate code stream mode according to the actual network environment.

3. Main menu:

 \sim

Preview: Real-time access to device video streams

Replay: remotely play the video stored on the device side

Remote settings: Remote sets the device

4. Mouse over to display the system user and web version information

Withdraw from web

5. Manual Alarm: Manually open or close the IO alarm




Color settings: Click to display or hide the color control.




AI alarm: Push the AI alarm events, click to check the AI push type, push the selected type

of AI alarm events, and click to empty the current push list



PTZ control: Click to open or close the PTZ Operation menu.



Direction arrow: Click to turn the PTZ camera

Default cruise

PTZ speed: Set the speed at which the PTZ camera rotates.

Zoom: Click- - / + to zoom in or out.

Aperture: Click to adjust the aperture size.


Focus: Click- - / + to adjust the focus.

It is the 3 DPTZ focus, it is the automatic focus, it is the areset preset point, it is the watch mode

PTZ rotation mode, with six modes: PTZ, PRESET, Line Scan, Watch Mode, Tour, and Pattern Scan.

Cruise: Start / stop the head cruise

Preset point: modify the preset point name, go to, add, and delete the preset point.




Watch Mode Page:

Time Interval: Watch wait time, stop operation to continue watch action

The interval time Mode: Select the watch mode , you can choose the default, preset point, linear scan, track cruise, pattern scan.

Click to start the cruise.




Line Scan Page:

Area scan: Click the record start position, turn HighSpeed Dome, and click the record end position.

Speed: Select the linear cruise speed.

Click to start the linear cruise, and High-Speed Dome


moves only in the same level schedulee in this mode.



Tour page:
Time Interval: Dwell time of each preset point

Click Add Preset, click Delete, click Up

/ Down, and click Start Cruise.



Pattern Scan Page:


Record: Click to start recording the cruise route, and click to stop recording.

Cruise: Click to start cruising following the previously recorded route and action.

6. Live View Control Buttons ① × The channel window switches over the display mode Open all the channel previews Close all channel previews Original proportion: Display the live video according to the original proportion Stretch: Stretch live video to fit the entire area of each channel on the screen Zoom in the web client to full screen Manual recording: Click to start a manual recording for all of the display channels. Click again to stop the recording. Manual video recording is saved to the computer Manual capture: click to grab the picture of all the current display channels to save to the computer Electronic zoom: Click on an active image, then click-drag over an area of the active image to zoom in. Right-click to return to the normal display. Volume control: by adjusting the volume of the level. Silent mode Intertext icon: Click Open the intercom between the client and the device, and click close the intercom with the device again (Note: this function requires the device to support the intercom function) White light control, can manually turn on the white light deterrence (need camera support). Warning alarm control, can manually open the alarm warning (need camera support). Red and blue light control, can manually open the red and blue light warning (need camera support). Area focus, click the button, use the mouse to preview the area, the camera lens will focus according to the sliding area.(Zoom camera support only) Click on the Add a Custom Tab event. Privacy mode (requires camera support). 7. Switch to the display paging

8.3.2 Playback


This page can search and replay videos stored in the device's hard disk, and can download videos to the PC.



Search video:

- 1. Click on the upper right corner to play back the Playback, and the icon enters the playback interface
- **2.** Select the date to query the video on the calendar. Days with video recording are shown as red underlined.
- **3.** Select the type of video to query in the Type.
- 4. Select the video stream that you need to search for and play to.
- 5. Check the channel back in the "channel".(Up to four channels simultaneously)
- **6.** Click on the search element Search icon to search for the video.
- 7. the video of the search will be displayed on the timeline. Click the video clip you want to start playing, and then click the play icon to play the video.

8.3.2.1 General Playback



- Single video is suspended
- Stop playing a single-channel video recording
- Play by frame: the first frame and move by playback. Available only when the Sync playback option is not selected.
- Sync play: Click to synchronously play the selected channel simultaneously at the same time
- Click to select a playing channel, and then click the recording icon to record the current video to the computer. Click again to stop the recording.
- Click on one of the channels that are playing, then click the capture icon to take a snapshot and save to the computer.
- Open the Download menu to download a video of the selected type of time for the selected channel.

	Start Time	End Time	Status	File Size
1	2025-07-29 09:43:59	2025-07-29 09:44:57	Not Downloaded	7.84M
2	2025-07-29 09:44:57	2025-07-29 09:52:18	Not Downloaded	58.39M
3	2025-07-29 09:52:18	2025-07-29 09:52:57	Not Downloaded	5.28M
4	2025-07-29 09:52:57	2025-07-29 09:59:57	Not Downloaded	55.52M
5	2025-07-29 09:59:57	2025-07-29 10:00:41	Not Downloaded	6.01M
6	2025-07-29 10:00:41	2025-07-29 10:01:35	Not Downloaded	7.39M
7	2025-07-29 10:01:35	2025-07-29 10:02:08	Not Downloaded	4.48M
8	2025-07-29 10:02:08	2025-07-29 10:02:43	Not Downloaded	4.76M
9	2025-07-29 10:02:43	2025-07-29 10:03:12	Not Downloaded	4.09M
10	2025-07-29 10:03:12	2025-07-29 10:03:43	Not Downloaded	4.30M
11	2025-07-29 10:03:43	2025-07-29 10:06:08	Not Downloaded	19.30M
12	2025-07-29 10:06:08	2025-07-29 10:06:45	Not Downloaded	5.01M
13	2025-07-29 10:06:45	2025-07-29 10:11:10	Not Downloaded	35.21M
	2025-07-29 10:11:10	2025-07-29 10:11:46	Not Downloaded	5.07M

Select the file to download, press the Start Download icon to start the download, and will display the download status. Press the Stop Download icon to stop downloading.

- Cut the backup, and download the video button of the cut time period to the PC local.
- Back forward, only available when the sync playback option is not selected.
- Playback speed: Click to select the play speed.
- Play all channels: Click Play all channels for select search. Available only when the Sync playback option is not selected.
- Stop playing all channels: Click to stop playing all channels. Available only when the Sync playback option is not selected.

Electronic zoom: Click the video you are playing, and then click and drag an area of the video to zoom in. Right-click to return to the normal display.


Original scale: Display the video being played in the original scale.

Itretch: Stretch the played video to fit the entire area of each channel on the screen.

Zoom in the web client to full screen play.

8.3.2.2 Picture Playback

After the device sets the picture, the pictures captured by the device can be searched on this page. Maximum of 5000 pictures can be searched for a single time, and the time interval can be modified according to the need.




Search capture map:

- 1. Click on the Playback in the top right corner of the window.
- 2. Select Picture from the drop-down menu in the upper left corner.
- 3. Select a date search on the calendar, with a red underline.
- **4.** Select the type of image to search from the list in the Search Type menu.
- 5. Check the channel to search for the video.
- **6.** Click on the Search.
- 7. The picture that meets the search criteria will be displayed on the right side. When double-clicking , the playback video of the time period before and after the picture will be played, and click to return to the previous interface.


8.3.2.3 Smart playback

The device will be marked as a smart type when it detects a change in the screen, and it can search for a Smart Playback video.



Click to display smart setting area, click to select all areas, click to clear all selected areas.


8.3.2.4 Tag playback



This page searches for all the added tags and ed, plays back, or removes them. Select the time and channel and click on the Search to complete the search. Click to jump to the position marked by the label for playback.


8.3.2.5 Al playback

After the device opens the AI alarm, the AI alarm event search can be conducted on this page, including face detection, license plate detection, pedestrian and vehicle detection, PID & LCD, repeat customers and face attendance type events.




8.3.3 Remote Settings

This interface supports remote configuration of device parameters, and channel, video recording, storage, alarm, event, network and system parameters.



8.3.4 Local settings

Set the download location for videos and snapshots taken through the Web client and select File Type for the video file.



Record Path (Manual recording path): Click Browse and select the folder where you need to save the manual recording on the computer.

Download Path (Video download path): Click Browse and select the folder you need to save to the computer.

Snapshot Path (Grab path): Click Browse and select the folder where you want to save the manual captured snapshot on your computer.


File Type (File type): Select the manual video recording file type.

Save (Save): Click to save the modification.

Chapter 9 Play the backup video


This section will help users to play video files backed up from the device using the Risco Video player. Computer system minimum requirements

- Intel I3 and above CPU
- Microsoft Systems 7 / 8 / 10 / 11, MacOS 10 and above
- And 8GB of memory
- 1. Install the video playback software in the CD and run it.



- **2.** Copy the backup files to your computer.
- 3. Click the Open file Open File icon or click the + icon in the playlist to load a single or multiple video files. It supports adding and playing the ". avf ",".avi ",". The mp4 " format file. Click on the icon to load the backed-up video folder.


Video Player Control




1.Playlist

- + Add file
- Deleted file
- Select play mode: play a single file and stop. play all listed files in order. play one file repeatedly and play all files repeatedly
 - TFilter by file name
 - 2.Hide / display the playlists
 - △ Click to Open the file or to load the folder
 - 3. play control
 Play
 - Pause
 - Stop playing
 - Play by frame: Click to play a video
 - Slow playback: 1 can set 1/2, 1/4, 1/8 and 1/16 times playback
 - Fast forward: You can set x2, x4, x8 and x16 times of playback
 - Volume control
- Multi-screen playback: you can play multiple videos at a time. When you select Multiple Screen Play, you can drag and drop videos from the Playlist to the Play screen.

- Snapshot
- Save a video clip to the computer. Press Start once and Press End the video clip again.
- Put the video player on the top
- The video window is displayed in full-screen
- The Advanced Settings menu selects the language of the player to configure the player function.



Basic Settings: Set the top-setting mode



Capture Settings: Set the save format and save path of the snapshot.

Chapter 10 XI Appendix

10.1 FAQs

1. What should I do if the hard disk is not detected?

A: If the system does not detect the hard disk, please check whether the data cable and the power cord are well connected, whether the interface on the motherboard is faulty, or whether the hard disk you use is supported.

- 2. After changing the system password, can accidentally forget and can not enter the system? A: When the administrator forgets the password, he can reset the device through the password retrieval function or restore the factory Settings through the physical reset button. It is recommended that users should set easy to remember and relatively secure passwords when setting the password.
- 3. Why is the power supply of the equipment and the camera normal but there is no video signal or abnormal images output at the monitor end?

Answer: Please check whether the network cable connection of the device is good, whether the network cable is used for too long and aging, or check whether the selection of N system / P system is consistent.

4. What is the influence of heat dissipation of the equipment?

Answer: The operation of the equipment will generate a certain amount of heat. Please place the equipment in a safe and well-ventilated place to avoid affecting the stability and service life of the system due to the high temperature of the equipment.

5. Why can the remote control of the device not be operated, while the monitoring screen is normal and the panel buttons can be used?

A: If the operation is aimed at the IR signal on the front panel of the body, but the remote control is still invalid, please check whether the battery in the remote control is normal and sufficient. If it is not the above problem, the remote control is broken.

6. If I put a hard drive on my PC into my device, can I use it?

A: It is recommended to use the special hard disk for video surveillance to avoid affecting the stable operation of the equipment.

7. Can you play it back along with the video?

A: Yes, the local system can support the recording back at the same time.

8. Can you clear some video records on the hard disk?

A: Considering the security of the file, you can not clear part of the video. If you do need to delete all the videos, you can choose to format the hard disk.

9. Why can't you log in to the device client?

Answer: Please check whether the network connection mode configuration is correct, whether the RJ-45 interface contact is good, and then when the network login password switch is opened, please check whether your input account and password are correct.

1. What is it like not to find any recorded information when you put the video back?

A: Please check whether the data cable of the hard disk is well connected and whether the system time is being illegally adjusted. Try a few more times, if the above phenomenon still appears after the restart to check whether the hard disk is damaged.

2. Why can't the device control the cradle head?

A: There may be the following reasons:

- A) Forward PTZ fault.
- B) Incorrect setup, connection and installation.
- C) incorrect PTZ setup.

And d) the cradle head decoder protocol does not match the device protocol.

- E) The cradle head decoder address does not match the device address.
- 3. Why doesn't dynamic detection work?

Answer: Check whether the motion detection time and motion detection area settings are correct, and it is to check whether the sensitivity setting is too low.

13. Why doesn't the alarm work?

Answer: check whether the alarm setting, alarm line are correct, and whether the alarm input signal is correct.

14. Why does the buzzer keep chirping?

Answer: check the relevant setting of the alarm, whether the motion detection is open and detected, whether the I/O alarm is normally closed, and check the relevant hard disk alarm setting.

15. Why is the system still recording by pressing STOP or clicking "Stop recording" in the shortcut menu?

Answer: "STOP" or "Stop recording" can only stop the manual recording. modify the recording status of some time to no video. to stop the video recording, change the video mode to the timing or manual recording, and then stop the recording in the above way. Or to stop video can set the channel status in the video setting to close.

10.2 Use and maintenance

- 1. When the hard disk recorder is shut down, turn off the system in the software interface, and then turn off the power. Please do not directly turn off the power switch, so as not to avoid loss or even damage the hard disk data.
- 2. Ensure that the hard disk recorder is far away from the heat and source and place.
- **3.** Clean the dust deposited in the body regularly, and keep the box around the hard disk video recorder well ventilated to facilitate heat dissipation.
- **4.** Audio and video signal lines and RS-232, RS-485 and other interfaces, please do not plug plug, otherwise it is easy to damage these ports.
- **5.** Regularly check whether the hard disk power cord and data cable in the body are used for too long and aging.
- **6.** Try to avoid the impact of other circuits on audio and video signals, to prevent electrostatic or induced voltage damage to the hard disk damage.
- 7. If the interface connected to the network cable is often plugged, it is recommended that users replace the cable regularly to avoid unstable input signal.
- **8.** This is A Class A product. In a living environment, the product may cause radio interference. In this case, the users may need to take practical measures about the interference.

10.3 Random attachments (subject to the physical object)



Warning:

If the wrong battery is replaced, there is a risk of an explosion Handle the used battery according to the instructions

Standard Limited Product Warranty ("Limited Warranty")

RISCO Ltd. ("RISCO") guarantee RISCO's hardware products ("Products") to be free from defects in materials and workmanship when used and stored under normal conditions and in accordance with the instructions for use supplied by RISCO, for a period of (i) 24 months from the date of delivery of the Product (the "Warranty Period"). This Limited Warranty covers the Product only within the country where the Product was originally purchased and only covers Products purchased as new.

Contact with customers only. This Limited Warranty is solely for the benefit of customers who purchased the Products directly from RISCO or from an authorized distributor of RISCO. RISCO does not warrant the Product to consumers and nothing in this Warranty obligates RISCO to accept Product returns directly from end users who purchased the Products for their own use from RISCO's customer or from any installer of RISCO, or otherwise provide warranty or other services to any such end user directly. RISCO's authorized distributor or installer shall handle all interactions with its end users in connection with this Limited Warranty. RISCO's authorized distributor or installer shall make no warranties, representations, guarantees or statements to its end users or other third parties that suggest that RISCO has any warranty or service obligation to, or any contractual privy with, any recipient of a Product. Remedies. In the event that a material defect in a Product is discovered and reported to RISCO during the Warranty Period, RISCO shall accept return of the defective Product in accordance with the below RMA procedure and, at its option, either (i) repair or have repaired the defective Product, or (ii) provide a replacement product to the customer.

Return Material Authorization. In the event that you need to return your Product for repair or replacement, RISCO will provide you with a Return Merchandise Authorization Number (RMA#) as well as return instructions. Do not return your Product without prior approval from RISCO. Any Product returned without a valid, unique RMA# will be refused and returned to the sender at the sender's expense. The returned Product must be accompanied with a detailed description of the defect discovered ("Defect Description") and must otherwise follow RISCO's then-current RMA procedure published in RISCO's website at www.riscogroup.com in connection with any such return. If RISCO determines in its reasonable discretion that any Product returned by customer conforms to the applicable warranty ("Non-Defective Product"), RISCO will notify the customer of such determination and will return the applicable Product to customer at customer's expense. In addition, RISCO may propose and assess customer a charge for testing and examination of Non-Defective Product.

Entire Liability. The repair or replacement of Products in accordance with this Limited Warranty shall be RISCO's entire liability and customer's sole and exclusive remedy in case a material defect in a Product is discovered and reported as required herein. RISCO's obligation and this Limited Warranty are contingent upon the full payment by customer for such Product and upon a proven weekly testing and examination of the Product functionality.

Limitations. This Limited Warranty is the only warranty made by RISCO with respect to the Products. The warranty is not transferable to any third party. To the maximum extent permitted by applicable law, this Limited Warranty shall not apply and will be void if: (i) the conditions set forth above are not met (including, but not limited to, full payment by customer for the Product and a proven weekly testing and examination of the Product functionality); (ii) if the Products or any part or component thereof: (a) have been subjected to improper operation or installation; (b) have been subject to neglect, abuse, willful damage, abnormal working conditions, failure to follow RISCO's instructions (whether oral or in writing); (c) have been misused, altered, modified or repaired without RISCO's written approval or combined with, or installed on products, or equipment of the customer or of any third party; (d) have been damaged by any factor beyond RISCO's reasonable control such as, but not limited to, power failure, electric power surges, or unsuitable third party components and the interaction of software therewith or (e) any failure or delay in the performance of the Product attributable to any means of communication provided by any third party service provider, including, but not limited to, GSM interruptions, lack of or internet outage and/or telephony failure. BATTERIES ARE EXPLICITLY EXCLUDED FROM THE WARRANTY AND RISCO SHALL NOT BE HELD RESPONSIBLE OR LIABLE IN RELATION THERETO, AND THE ONLY WARRANTY APPLICABLE THERETO, IF ANY, ISTHE BATTERY MANUFACTURER'S WARRANTY. RISCO does not install or integrate the Product in the end user's security system and is therefore not responsible for and cannot guarantee the performance of the end user's security system which uses the Product or which the Product is a component of.

This Limited Warranty applies only to Products manufactured by or for RISCO. Further, this Limited Warranty does not apply to any software (including operating system) added to or provided with the Products or any third-party software, even if packaged or sold with the RISCO Product. Manufacturers, suppliers, or third parties other than RISCO may provide their own warranties, but RISCO, to the extent permitted by law and except as otherwise specifically set forth herein, provides its Products "AS IS". Software and applications distributed or made available by RISCO in conjunction with the Product (with or without the RISCO brand), including but not limited to system software, as well as P2P services or any other service made available by RISCO in relation to the Product, are not covered under this Limited Warranty. Refer to the Terms of Service at: www.riscogroup.com/warranty for details of your rights and obligations with respect to the use of such applications, software or any service. RISCO does not represent that the Product may not be compromised or circumvented; that the Product will prevent any personal injury or property loss by burglary, robbery, fire or otherwise, or that the Product will in all cases provide adequate warning or protection. A properly installed and maintained alarm may only reduce the risk of a burglary, robbery or fire without warning, but it is not insurance or a guarantee that such will not occur or will not cause or lead to personal injury or property loss. CONSEQUENTLY, RISCOSHALL HAVE NO LIABILITY FOR ANY PERSONAL INJURY, PROPERTY DAMAGE OR OTHER LOSS BASED ON ANY CLAIM AT ALL INCLUDING A CLAIM THAT THE PRODUCT FAILED TO GIVE WARNING.

EXCEPT FOR THE WARRANTIES SET FORTH HEREIN, RISCO AND ITS LICENSORS HEREBY DISCLAIM ALL EXPRESS, IMPLIED ORSTATUTORY, REPRESENTATIONS, WARRANTIES, GUARANTEES, AND CONDITIONS WITH REGARD TO THE PRODUCTS, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATIONS, WARRANTIES, GUARANTEES, AND CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND WARRANTIES AGAINST HIDDEN OR LATENT DEFECTS, TO THE EXTENT PERMITTED BY LAW. WITHOUT LIMITING THE GENERALITY OF THE

FOREGOING, RISCO AND ITS LICENSORS DO NOT REPRESENT OR WARRANT THAT: (I) THE OPERATION OR USE OF THE PRODUCT WILL BE TIMELY, SECURE, UNINTERRUPTED OR ERROR-FREE; (ii) THAT ANY FILES, CONTENT OR INFORMATION OF ANY KIND THAT MAY BE ACCESSED THROUGH THE PRODUCT SHALL REMAIN SECURED OR NON DAMAGED. CUSTOMER ACKNOWLEDGES THAT NEITHER RISCO NOR ITS LICENSORS CONTROL THE TRANSFER OF DATA OVER COMMUNICATIONS FACILITIES, INCLUDING THE INTERNET, GSM OR OTHER MEANS OF COMMUNICATIONS AND THAT RISCO'S PRODUCTS, MAY BE SUBJECT TO LIMITATIONS, DELAYS, AND OTHER PROBLEMS INHERENT IN THE USE OF SUCH MEANS OF COMMUNICATIONS. RISCO IS NOT RESPONSIBLE FOR ANY DELAYS, DELIVERY FAILURES, OR OTHER DAMAGE RESULTING FROM SUCH PROBLEMS. RISCO WARRANTS THAT ITS PRODUCTS DO NOT, TO THE BEST OF ITS KNOWLEDGE, INFRINGE UPON ANY PATENT, COPYRIGHT, TRADEMARK, TRADE SECRET OR OTHER INTELLECTUAL PROPERTY RIGHT IN ANY EVENT RISCO SHALL NOT BE LIABLE FOR ANY AMOUNTS REPRESENTING LOST REVENUES OR PROFITS, PUNITIVE DAMAGES, OR FOR ANY OTHER INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, EVENIF THEY WERE FORESEEABLE ORRISCO HAS BEEN INFORMED OF THEIR POTENTIAL.

Contact Details

RISCO Group is committed to customer service and product support. You can contact us through our website (www.riscogroup.com) or at the following telephone and fax numbers:

United Kingdom	France	Israel
Tel: +44-(0)-161-655-5500 support-uk@riscogroup.com	Tel: +33-164-73-28-50 support-fr@riscogroup.com	Tel: +972-3-963-7777 support@riscogroup.com
Italy	Belgium (Benelux)	
Tel: +39-02-66590054	Tel: +32-2522-7622	
support-it@riscogroup.com	support-be@riscogroup.com	
Spain	China (Shanghai)	
Tel: +34-91-490-2133	Tel: +86-21-52-39-0066	
support-es@riscogroup.com	support-cn@riscogroup.com	





© RISCO Group 08/2025

5IN3149